

NEMA HP 8

**ELECTRICAL AND ELECTRONIC
CROSSLINKED, MODIFIED
LOW SMOKE POLYOLEFIN (XLPO)
INSULATED HOOK-UP WIRE,
TYPES LS (105°C-600 V), ZHDM
(90°C-600 V), ZHDH (90°C-600 V),
ZH (125°C-600 V), AND ZHX (125°C-
1000 V)**

NEMA Standards Publication HP 8-2009

Electrical and Electronic Crosslinked, Modified Low Smoke Polyolefin (XLPO) Insulated Hook-Up Wire, Types LS (105°C-600 V), ZHDM (90°C-600 V), ZHDH (90°C-600 V), ZH (125°C-600 V), and ZHX (125°C-1000 V)

Published by:

National Electrical Manufacturers Association

1300 North 17th Street, Suite 1752
Rosslyn, VA 22209

www.nema.org

© Copyright 2009 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

FOREWORD	III
SECTION 1 GENERAL	1
1.1 SCOPE	1
1.2 REFERENCE STANDARDS AND SPECIFICATIONS	1
1.3 RECOMMENDED USES OF WIRE TYPES	2
1.3.1 TYPE LS	2
1.3.2 TYPE ZHDM, and ZHDH	2
1.3.3 TYPE ZH	2
1.3.4 TYPE ZHX	2
1.4 PART IDENTIFICATION NUMBER (PIN)	3
SECTION 2 CONDUCTORS	5
2.1 CONDUCTOR MATERIALS	5
2.2 CONDUCTOR COATINGS	5
2.2.1 Tin-Coated Conductors	5
2.2.2 Silver-Coated Conductors	5
2.3 STRANDING	5
2.4 WIRE DIAMETER	5
2.5 CONDUCTOR SPLICES	5
SECTION 3 INSULATION	7
3.1 GENERAL	7
3.2 XLPO INSULATION	7
SECTION 4 WIRE IDENTIFICATION	10
4.1 CIRCUIT IDENTIFICATION	10
4.1.1 Lay of Stripes	10
4.2 IDENTIFICATION BY PRINTING	10
4.2.1 Identification of Product	10
SECTION 5 PHYSICAL AND ELECTRICAL REQUIREMENTS	11
5.1 GENERAL	11
5.2 QUALITY CONFORMANCE INSPECTION OF FINISHED PRODUCT	11
5.2.1 Definitions	11
5.2.1.1 Inspection Lot	11
5.2.1.2 Unit of Product	11
5.2.2 Sampling Inspection	11
5.3 WORKMANSHIP	11
5.4 MATERIALS CERTIFICATION	11
SECTION 6 TEST PROCEDURES	13
6.1 PHYSICAL TESTS	13
6.1.1 Test Temperature	13
6.1.2 Heat Resistance	13
6.1.3 Insulation Tensile Strength and Elongation	13
6.1.4 Dimensional Inspection	13
6.1.4.1 Conductor Diameter	13
6.1.4.2 Insulation Diameter	13
6.1.4.3 Concentricity	13
6.1.5 Shrinkage	14
6.1.6 Flammability	14
6.1.7 Heat Aging Test	14

6.1.8	<i>Fungus Resistance</i>	14
6.1.9	<i>Cold Bend</i>	14
6.1.10	<i>Halogen Content</i>	14
6.1.11	<i>Smoke Index</i>	14
6.1.12	<i>Toxicity Index</i>	15
6.1.13	<i>Acid Gas Generation</i>	15
6.2	ELECTRICAL TESTS	15
6.2.1	<i>Conductor Resistance</i>	15
6.2.2	<i>Spark or Impulse Test</i>	15
6.2.3	<i>Dielectric Strength</i>	15
6.2.4	<i>Insulation Resistance</i>	15
6.2.5	<i>Characteristic Impedance</i>	15
SECTION 7	NOTES	16
7.1	PACKAGING REQUIREMENTS	16
7.2	LABELING	16
7.3	LENGTHS.....	16
SECTION 8	ORDERING DATA	17
8.1	ORDERING INFORMATION	17

Tables

TABLE 1-1	CONDUCTOR MATERIAL AND COATING	3
TABLE 1-2	AWG NOMINAL CONDUCTOR SIZE	3
TABLE 1-3	NUMBER OF STRANDS	3
TABLE 1-4	COLOR (SEE PARA 4.1)	4
TABLE 2-1		6
TABLE 3-1	DIMENSIONS-TYPE WIRES	7
TABLE 3-2	IMPEDANCE PROPERTIES OF TWISTED PAIR CABLES FOR TYPE ZHDM AND ZHDH WIRES TESTED AT 1 MHZ	9
TABLE 4-1	LENGTH OF LAY OF STRIPES	10
TABLE 5-1	PHYSICAL AND ELECTRICAL REQUIREMENTS FOR TYPE LS, ZHD, ZH, AND ZHX WIRES	12
TABLE 7-1	MINIMUM LENGTHS	16

Foreword

This Standards Publication was developed by the NEMA High Performance Wire and Cable Section to define hook-up cables using low smoke and low or zero halogen insulation materials that could be used as a possible alternative to PVC insulated cables for applications requiring these types of characteristics.

In the preparation of this Standards Publication, input of users and other interested parties has been considered. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product Subdivision by contacting the:

Vice President, Technical Services
National Electrical Manufacturers Association
1300 North 17th Street, Suite 1752
Rosslyn, Virginia 22209

Section approval of the standard does not necessarily imply that all section members voted for its approval or participated in its development. At the time it was approved, the Section was composed of the following members:

AFC Cable Systems—New Bedford, MA
AmerCable—El Dorado, AR
American Insulated Wire Corporation—Pawtucket, RI
Belden CDT, Inc.—St. Louis, MO
Berk-Tek a Nexans Company—Elm City, NC
Cable USA, Inc.—Naples, FL
Coleman Cable Inc.—Waukegan, IL
Draka Comteq USA Inc.—Franklin, MA
Fisk Alloy Conductors, Inc.—Hawthorne, NJ
General Cable—Highland Heights, KY
Harbour Industries, Inc.—Shelburne, VT
Judd Wire, Inc.—Turners Falls, MA
Kaneka High-Tech Materials, Inc.—Pasadena, TX
Leoni Wire, Inc.—Chicopee, MA
Leviton Manufacturing Co., Inc.—Gardena, CA
Phelps Dodge High Performance Conductors—Inman, SC
Quirk Wire Company, Inc.—West Brookfield, MA
Radix Wire Company—Euclid, OH
Rea Magnet Wire Company, Inc.—Fort Wayne, IN
Rockbestos-Surprenant Cable Corporation—East Granby, CT
Southwire Company—Carrollton, GA
Specialty Cable Corporation—Wallingford, CT
The Monroe Cable Company, Inc.—Middletown, NY
The Okonite Company—Ramsey, NJ
Tyco Electronics/Raychem Wire & Cable—Menlo Park, CA

< This page is intentionally left blank. >

Section 1 GENERAL

1.1 SCOPE

This Standards Publication covers specific requirements for crosslinked, modified polyolefin insulated solid and stranded wire, designed to the internal wiring of high reliability electrical and electronic equipment. This Standards Publication addresses 600 volt (Type LS, ZHDM, ZHDH, ZH), and 1000 volt (Type ZHX) wire and permits continuous conductor temperature ratings of -40°C to + 90°C, 105°C, or 125°C with either tin- or silver-coated conductors. These types of hook-up wire are used when the following requirements are called for:

- Moderate temperature resistance
- Low temperature resistance
- Good Dielectric Constant (Type ZHDM, and ZHDH)
- Moderate Dielectric Constant (Type LS)
- Good Flexibility and flex life when stranded conductors are used
- Solder iron resistance for easier solder terminations without potential damage
- Low Smoke (Types LS, ZHDM, ZHDH, ZH, ZHX)
- Zero Halogen (Types ZHDM, ZHDH, ZH, ZHX)
- Low Toxicity (Types LS, ZHDM, ZHDH, ZH, ZHX)
- Low Acid Gas Generation (Types LS, ZHDM, ZHDH, ZH, ZHX)