

**NEMA Standards Publication TS 4-2005**

*Hardware Standards for Dynamic Message Signs (DMS)  
With NTCIP Requirements*

*Published by:*

**National Electrical Manufacturers Association**

1300 North 17th Street, Suite 1847

Rosslyn, Virginia 22209

[www.nema.org](http://www.nema.org)

© Copyright 2005 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

## **NOTICE AND DISCLAIMER**

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

## CONTENTS

		Page
Foreword .....		vii
History and Acknowledgements .....		viii
<b>Section 1</b>	<b>GENERAL</b>	
1.1	Scope and Introduction.....	1
1.2	General Statements.....	2
1.3	Types of DMS Signs.....	2
	1.3.1 Variable Message Signs (VMS).....	2
	1.3.2 Changeable Message Signs .....	2
	1.3.3 Blankout Signs .....	3
1.4	Types of Technologies .....	3
1.5	References .....	3
1.6	Authorized Engineering Information .....	4
1.7	Glossary of DMS Terms .....	5
<b>Section 2</b>	<b>ENVIRONMENTAL REQUIREMENTS</b>	
2.1	Environmental and Operating Standards.....	20
	2.1.1 Definitions of Major Units of the DMS Equipment.....	20
	2.1.2 Compliance of Major Units .....	20
	2.1.3 Electrical.....	21
	2.1.4 Transients.....	22
	2.1.5 Temperature and Humidity.....	23
	2.1.6 Vibration .....	24
	2.1.7 Shock .....	24
	2.1.8 Time and Timing .....	25
2.2	DMS Equipment Tests.....	25
	2.2.1 Test Facilities (Except Vibration and Shock) .....	25
	2.2.2 Test Unit.....	25
	2.2.3 Test Functions.....	26
	2.2.4 Tests For Transients, Temperature, Voltage, and Humidity.....	26
	2.2.5 Test J: Vibration Test .....	32
	2.2.6 Test K: Shock (Impact) Test.....	33
	2.2.7 Test L: Power Interrupt Tests.....	34
	2.2.8 Test M: Timing Accuracy Tests.....	35
<b>Section 3</b>	<b>SIGN MECHANICAL CONSTRUCTION</b>	
3.1	General.....	37
	3.1.1 Weather-Tight Enclosure .....	37
	3.1.2 Temperature Control .....	37
	3.1.3 Sign Face .....	38
	3.1.4 Galvanic Protection .....	38
	3.1.5 Light Leaks .....	38
	3.1.6 Contrast Border.....	38
3.2	Fixed-Location Dynamic Message Signs .....	38
	3.2.1 Structural Integrity .....	39
	3.2.2 Aluminum Housings .....	39
	3.2.3 Housings Made of Other Materials .....	40
	3.2.4 Front and Rear Access Front and Rear Access DMS .....	40
	3.2.5 Front Access DMS .....	40
	3.2.6 Rear Access DMS.....	40

	3.2.7	Walk-In Access DMS .....	40
	3.2.8	Convenience Outlets, All Housings.....	41
3.3		Portable DMS .....	42
	3.3.1	Transport Safety.....	42
	3.3.2	Structural Integrity .....	42
	3.3.3	Major Subsystems.....	43
	3.3.4	Corrosion Protection and Finishes.....	43
	3.3.5	Power Sources.....	44
<b>Section 4</b>		<b>CONTROLLER TO SIGN INTERFACE</b>	
4.1		Interface with Sign Housing.....	45
4.2		Wiring .....	45
4.3		Wire Entrances.....	45
4.4		Pixel Control Wiring.....	45
	4.4.1	Power Supply Locations.....	45
	4.4.2	DMS Controller and Driver Module Locations .....	46
<b>Section 5</b>		<b>DISPLAY PROPERTIES</b>	
5.1		General.....	47
	5.1.1	Development Sources.....	47
	5.1.2	Legibility Versus Visibility .....	47
	5.1.3	Photometric and Colorimetric Requirements .....	47
5.2		Contrast Ratio.....	47
5.3		Cone of Vision Type Classification.....	49
	5.3.1	Light Emitting Technology.....	49
	5.3.2	Reflective Technology.....	49
	5.3.3	Hybrid Technology .....	49
5.4		Luminance Intensity Requirements .....	50
	5.4.1	Luminous Intensity Uniformity.....	53
5.5		Chromaticity Classifications and Limits .....	53
	5.5.1	Chromaticity Limits.....	53
	5.5.2	Chromaticity Uniformity .....	56
5.6		Display Characters .....	56
	5.6.1	Fonts and Font Alphabets.....	56
	5.6.2	Required Fonts by Sign Type.....	56
5.7		Display Change Time .....	57
5.8		Moving Arrows.....	57
5.9		Test Methods.....	58
	5.9.1	General Test Parameters.....	58
	5.9.2	Test Area.....	59
	5.9.3	Considerations for Precision and Bias of Test Methods and Accuracy of Test Results .....	61
<b>Section 6</b>		<b>OPTICAL COMPONENTS</b>	
6.1		General.....	62
	6.1.1	Pixel Spacing.....	62
	6.1.2	Character Module Spacing .....	62
	6.1.3	Interchangeability of Character Modules .....	62
	6.1.4	Character Module Replacement .....	63
6.2		Shuttered Fiber Optic Light System .....	63
	6.2.1	General.....	63
	6.2.2	Fiberoptic Harnesses .....	63
	6.2.3	Lamp Assembly.....	63
	6.2.4	Light Filter.....	63
	6.2.5	Shutter System.....	64
6.3		LED Light System.....	64

	6.3.1	General.....	64
	6.3.2	LED Selection.....	64
	6.3.3	LED Use.....	64
6.4		Fiber Optic Hybrid Light System.....	64
	6.4.1	General.....	64
	6.4.2	Requirements.....	64
6.5		LED Hybrid Light System.....	65
	6.5.1	General.....	65
	6.5.2	Requirements.....	65
<b>Section 7</b>		<b>DMS CONTROLLER CABINET</b>	
	7.1	General.....	66
	7.2	Cabinet Design.....	66
	7.2.1	Layout.....	66
	7.2.2	Protection.....	66
<b>Section 8</b>		<b>ELECTRONICS AND ELECTRICAL</b>	
8.1		Electronic Components.....	67
	8.1.1	General.....	67
	8.1.2	Interchangeability.....	67
8.2		Components.....	67
	8.2.1	General.....	67
	8.2.2	Electronic Components.....	67
	8.2.3	Capacitors.....	68
	8.2.4	Potentiometers.....	68
	8.2.5	Resistors.....	68
	8.2.6	Semiconductor Devices.....	68
	8.2.7	Transformers and Inductors.....	68
	8.2.8	Triacs.....	68
	8.2.9	Circuit Breakers.....	68
	8.2.10	Fuses.....	68
	8.2.11	Switches.....	69
	8.2.12	Wiring, Cabling, and Harnesses.....	69
	8.2.13	Controller Indicators and Character Displays.....	69
	8.2.14	Connectors.....	69
8.3		Mechanical Requirements.....	69
	8.3.1	Assemblies.....	69
	8.3.2	PCB Design and Connectors.....	69
	8.3.3	Model Numbers.....	70
	8.4	Printed Circuit Boards.....	70
	8.4.1	Design, Fabrication, and Mounting.....	70
	8.4.2	Soldering.....	70
8.5		Location and Provisions of Driving Electronics.....	70
	8.5.1	General.....	70
	8.5.2	Shuttered Fiber Optic Signs.....	70
	8.5.3	LED Signs.....	70
	8.5.4	Fiberoptic Hybrid Signs.....	70
	8.5.5	LED Hybrid Signs.....	70
8.6		Cabinet Wiring.....	71
8.7		Communication.....	71
	8.7.1	Communication Interfaces.....	71
	8.7.2	Communications.....	71
8.8		Brightness Controls.....	71
	8.8.1	Ambient Light Sensing and Dimming Control.....	72
8.9		DMS Controller Electronics.....	72
	8.9.1	General.....	72

8.9.2	Central Processor Unit.....	72
8.9.3	Input/Output.....	72
8.9.4	Internal Clock.....	72
8.9.5	Watchdog Timer.....	73
8.9.6	Loss of Power.....	73
8.9.7	Communications Link Monitor.....	73
8.9.8	Manual Test Interface.....	73
8.9.9	Controller Reset Switch.....	73
8.10	Controller Functions.....	73
8.10.1	General.....	73
8.10.2	Control Architectures.....	73
8.10.3	Common Functionality.....	74
8.10.4	Centralized Messaging Architecture.....	74
8.10.5	Local Messaging Architecture.....	74
8.10.6	Display Writing.....	75
8.10.7	NTCIP Protocol and Command Sets.....	75
8.10.8	Other Protocols and Command Sets.....	75
8.11	Local Control.....	75
<b>Section 9 PERFORMANCE MONITORING</b>		
9.1	Display Diagnostics and Monitoring.....	76
9.1.1	Incandescent Lamp Tests.....	76
9.1.2	Shutter and Disk Monitoring Pixel Service.....	76
9.1.3	LED Pixel Tests.....	76
9.1.4	LED Temperature Monitor.....	76
9.2	Controller Diagnostics and Monitoring.....	77
9.2.1	Watchdog Timer.....	77
9.2.2	Results of Controller Failures.....	77
9.2.3	Power Line Failures.....	77
9.2.4	Communication Link Failures.....	77
9.2.5	Subsystem Component Communications.....	77
9.3	Error and Failure Log.....	77
9.4	Message Verification.....	78
<b>Section 10 POWER REQUIREMENTS</b>		
10.1	AC or DC Electrical Service.....	79
10.2	Power Panels for AC Only.....	79
10.2.1	Minimum Requirements.....	79
10.2.2	Service Drop Advisory.....	79
10.3	Distribution Panels for DC.....	79
10.4	Ground to Neutral Isolation.....	79
10.5	Surge Protection Device.....	79
10.6	Convenience Outlets AC Only.....	79
10.7	Calculated Electrical Load.....	80
<b>Section 11 CONFORMANCE</b>		
11.1	General.....	81
11.1.1	Involved Parties.....	81
11.1.2	Other.....	81
11.2	Conformance Document Types.....	81
11.2.1	Certificates.....	81
11.2.2	Conformance Testing.....	81
11.2.3	Statement.....	81
11.2.4	Inspections.....	82
11.2.5	Evaluation.....	82
11.3	Requirements.....	82

11.3.1	Mandatory .....	82
11.3.2	Optional .....	82
11.4	Conformance Documentation Requirements .....	82
11.5	Conformance Table .....	83
<b>Section 12 DOCUMENTATION</b>		
12.1	Drawing Documentation .....	90
12.1.1	System Diagrams .....	90
12.1.2	Wiring Diagrams .....	90
12.1.3	Mechanical Drawings .....	90
12.2	Site Specific Documentation .....	90
12.2.1	Conformance table checklist .....	90
12.2.2	NTCIP MIB file .....	90
12.2.3	As-built Documentation .....	90
12.2.4	Configuration Information .....	91
12.2.5	Rev Numbers .....	91
12.2.6	Test Results .....	91
12.2.7	Product Burn-In .....	91
12.3	Manuals .....	91
12.3.1	Service .....	91
12.3.2	Troubleshooting .....	91
12.3.3	Operator's Manual .....	91
12.4	Warranty Documentation .....	91

### Figures

2-1	Compliance of Major Units .....	21
2-2	Operating Voltages .....	21
2-3	Transient Requirements .....	23
2-4	Wet-Bulb, Dry-Bulb Relative Humidity at Barometric Pressure of 29.92 in. of Mercury .....	21
2-5	Test Functions .....	26
5-1	Geometric Configuration of Test Equipment for Determination of Luminance and Contrast for All Technologies and Chromaticity of Light Emitting and Hybrid Technologies .....	58
5-2	Geometric Configuration of Test Equipment for Determination of Chromaticity of Reflective Technology .....	58
5-3	Layout Examples for a Test Module and the Positioning of the Measuring Area (Circle) .....	60

### Tables

2-1	Test Profile .....	29
2-2	Operating Voltages .....	20
2-3	Transient Requirements .....	22
2-4	Wet-Bulb Dry-Bulb Relative Humidity At Barometric Pressure of 29.92 In. Hg. ....	23
5-1	Minimum Contrast Ratio Requirements, Yellow .....	48
5-2	Minimum Contrast Ratio Requirements, White .....	48
5-3	Minimum Contrast Ratio Requirements, White/Yellow .....	48
5-4	Minimum Contrast Ratio Requirements, Green .....	48
5-5	Minimum Contrast Ratio Requirements, Red .....	48
5-6	Minimum Contrast Ratio Requirements, Blue .....	49
5-7	Cone of Vision Type Classification .....	50
5-8	Luminance Intensity Limits in CD/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Yellow .....	51
5-9	Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for White .....	51
5-10	Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for White/Yellow .....	51
5-11	Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical)	

Test Angles—for Green.....	52
5-12 Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical)	
Test Angles—for Yellow/Green .....	52
5-13 Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical)	
Test Angles—for Red .....	52
5-14 Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical)	
Test Angles—for Orange.....	53
5-15 Luminance Intensity Limits in Cd/M <sup>2</sup> for On-Axis (0° Horizontal, 0° Vertical)	
Test Angles—for Blue.....	53
5-16 Chromaticity Limits for Light Emitting DMS Technology .....	54
5-17 Chromaticity Limits for Reflective DMS Technology .....	55
5-18 Chromaticity Limits for Hybrid DMS Technology .....	55

## FOREWORD

This NEMA Standards Publication, TS 4-2004, *Hardware Standards for Dynamic Message Signs (DMS), with NTCIP Requirements*, was developed as a design and implementation guide for dynamic traffic messaging equipment that can be safely installed and provided to the end user with operational features based on current technology. Within the standard, any reference to a specific manufacturer is strictly for the purpose of defining interchangeability where there exists no nationally recognized standard covering all the requirements. The manufacturer references do not constitute a preference. The TS 4 Standards Publication is intended to reduce hazards to persons and property when traffic-messaging equipment is properly selected and installed in conformance with the requirements herein.

The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to the validity of any claims or of any patent rights in connection therewith.

In the preparation of this Standards Publication, input of users and other interested parties has been sought and evaluated. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product Subdivision by contacting the:

Vice President, Technical Services  
National Electrical Manufacturers Association  
1300 North 17th Street  
Rosslyn, Virginia 22209

The Dynamic Message Sign Technical Committee developed this standard at the request of the NEMA Transportation Management Systems and Associated Control Devices Section of which it is a part. Section approval of the standard does not necessarily imply that all Section members voted for its approval or participated in its development. At the time it was approved, the Transportation Management Systems and Associated Control Devices Section was composed of the following members:

3M, Intelligent Transportation Systems  
ADDCO, Inc.  
American Signal Company  
DAKTRONICS, Inc.  
Eberle Design, Inc.  
Econolite Control Products, Inc.  
Fiberoptic Display Systems, Inc.  
Image Sensing Systems, Inc.  
Iteris, Inc.  
McCain Traffic Supply, Inc.  
P.B. Farradyne, a Division of Parsons Brinckerhoff Quade and Douglas, Inc.  
Peek Traffic Corporation  
Safetran Traffic Systems, Inc.  
Siemens Intelligent Transportation Systems  
Skyline Products, Inc.

## HISTORY AND ACKNOWLEDGEMENTS

As the implementation of variable message signing and general light emitting technology increased in the United States during the late 1980s and early 1990s, various transportation departments tried a number of diverse technologies to meet their signing needs. This eventually led to a wide variety of specifications developed across the country, a number of opposing philosophies for implementation by the users, and some unsubstantiated claims by manufacturers. It also led to conflicting definitions and references from one agency to the next for what constituted a variable message sign (VMS) or its use.

In 1995, in response to a request by Mr. Crawley Parris of NEMA seeking VMS manufacturers to become members of the NEMA 3-TS Transportation Section, several companies joined NEMA. In August of that year, a proposal was made to the Transportation Section (now the Transportation Management Systems and Associated Control Devices Section) to create this hardware standard for signing. However, at that time, the NTCIP effort was expanding, and the FHWA was hoping for considerable input from NEMA companies to develop the NTCIP protocol.

Since the same companies would be involved in both efforts and resources were limited, it was decided within NEMA to table the work for the NEMA hardware standard until the NTCIP VMS object definitions were created. The NEMA Committee to work on the object definitions held its first meeting in September 1995 and eventually submitted draft version 1.14 of NEMA TS 3.6-1997 in March of 1997. With some minor editorial modification, this version of object definitions eventually became NTCIP 1203:1997, released in December 1999. This was the first combined standard to be approved by the three SDOs of NTCIP.

In August 1997, the VMS manufacturers formed a new committee of the NEMA Transportation Section and met for the first time to outline a plan for developing this hardware standard. The initial outline included plans to define the hardware requirements for all the various types of implementations of variable type signage that are used in the transportation industry, such as changeable message signs, blankout signs, etc. However, once actual work began, user requests became urgent to get a standard in use, so it was decided to initially work on the VMS parts of the hardware only, and to table the other parts for future versions.

The table below gives the schedule of meetings and attendance by the NEMA member companies and DMS manufacturers.

NEMA Member Co. (*)		*		*	*	*	*		*	*	*	*	
Attending Company (P)		ADDCO	Adaptive Micro Systems*	American Signal	3M – ITS	Daktronics	Fiberoptic Display Systems	Mark IV	McCain Traffic Supply	PB Farradyne	Skyline Products	Viggens/Iteris/Trevion	Vultron***
Meeting Date	Location												
Aug. 6, 1997	Boston	P			P	P	P	P			P		P
Dec. 2-4, 1997	Tucson	P			P	P	P	P	P		P		P
Mar. 24-25, 1998	Las Vegas	P			P		P	P**			P		P
Jun. 2-3, 1998	Denver	P					P	P**					P
Aug. 11-12, 1998	Toronto	P			P	P	P	P**				P	
Dec. 9, 1998	Houston				P		P	P**					
Mar. 30-31, 1999	Las Vegas						P	P**					P
Jun. 15-16, 1999	Chicago	P			P	P	P						P
Oct. 19-20, 1999	Rhode Island	P					P	P**			P		
Jan. 11-12, 2000	NEMA	P		P	P		P						
Apr. 18-19, 2000	Seattle	P		P	P	P	P						
Jun. 13-14, 2000	St. Paul	P		P		P	P	P**					
Sep. 19-20, 2000	Las Vegas	P		P		P	P	P**			P		
Nov. 14-15, 2000	Atlanta			P			P	P**					
Feb. 6-7, 2001	Houston	P		P		P	P	P**					
May 21-23, 2001	NEMA			P		P	P	P**					
Jul. 16-18, 2001	Toronto	P		P	P	P		P**					
Sep. 13, 2001	Telecon	P		P	P	P	P			P			
Nov. 13-15, 2001	Rhode Island	P		P	P		P	P**			P		
Feb. 4-6, 2002	Las Vegas	P		P	P		P		P	P	P		
Apr. 17, 2002	Telecon	P		P	P	P	P		P		P		
May 21-23, 2002	Idaho	P	P	P	P		P		P				
Jun. 25, 2002	Telecon	P			P		P		P				
Jul. 22, 2002	Telecon	P		P			P		P		P		
Aug. 27, 2002	Telecon	P		P	P		P		P		P		
Sep. 24, 2002	Telecon	P		P	P		P		P		P		
Oct. 8, 2002	Telecon	P		P			P		P				
Oct. 10, 2002	Telecon	P			P		P		P				
Nov. 13, 2002	Telecon	P		P	P		P		P		P		
Jan. 13, 2002	Washington, DC	P			P		P			P			
Feb. 12, 2003	Telecon	P		P	P		P				P		
Apr. 3, 2003	Telecon			P	P		P						
Apr. 17, 2003	Telecon			P	P		P		P		P		
May 13, 2003	Telecon			P	P		P		P		P		
Jun. 10, 2003	Telecon						P		P		P		
Jun. 20, 2003	Telecon			P	P		P		P		P		
Aug. 20, 2003	Telecon	P			P	P	P		P		P		

NEMA Member Co. (*)		*		*	*	*	*		*	*	*	*	
Attending Company (P)	Location	ADDCO	Adaptive Micro Systems*	American Signal	3M – ITS	Daktronics	Fiberoptic Display Systems	Mark IV	McCain Traffic Supply	PB Farradyne	Skyline Products	Viggens/Iteris/Trevion	Vultron***
Meeting Date	Location												
Oct. 2, 2003	Telecon	P				P	P		P		P		
Oct. 14, 2003	Telecon	P				P	P		P		P		
Nov. 4, 2003	Telecon	P				P	P		P		P		
Nov. 6, 2003	Telecon	P			P	P	P		P		P		
Nov. 18, 2003	Telecon	P			P	P	P		P				
Dec. 19, 2003	Telecon	P			P	P	P		P		P		
Jan. 8, 2004	Telecon	P			P	P	P		P		P		
Jan. 20, 2004	Telecon	P			P	P	P		P		P		
Jun. 2, 2004	Telecon	P				P	P				P		
Jun. 15, 2004	Telecon	P					P						
Jun. 23, 2004	Telecon	P				P	P				P		
Nov. 9, 2004	Telecon	P					P						

NOTES—

- \* Non-member
- \*\* Paid to attend meeting.
- \*\*\* NEMA membership lapsed

## **Section 1 GENERAL**

### **1.1 SCOPE AND INTRODUCTION**

The goal of this standard is to provide the user with safe, dependable, functional, and easily maintained Dynamic Message Sign (DMS) equipment.

The requirements of this standard were developed by industry consensus, taking into account current user needs, available commercial technologies, engineering research, traffic engineering applications, human factors engineering, and engineering judgment.

NEMA Bylaws require the periodic review and updating of this standard. Further updates should include the evaluation of new technologies and research.

Original quantitative research is not within the scope or resources of this committee. Said research by others is encouraged and should be considered by the reviewing committee in support of the updating process.

The scope of this document is to define the minimum hardware and functional characteristics of electronically controlled Dynamic Message Signs used for displaying messages to travelers.

The intent of this standard is to eventually accommodate all subsets of the DMS family. However, this initial version predominantly addresses the Variable Message Sign subset.

In preparing this standard, the committee began with a very comprehensive and encompassing scope of work that was later trimmed so the standard could be released at an earlier date. For almost every element described, arguments could be made to include additional information or less information.

Rather than debate these issues internally and eternally within the Committee, the consensus was that greater benefit would be served from end user input derived through a first implementation of a standard with a reduced scope. With this in mind, the committee anticipates that a second, market driven version of this standard will include further end user input discovered from implementations and other work on the items intentionally tabled from this version.

In all cases, the goal was to avoid, as much as possible, "specification" language that detailed how an item must be built, in favor of "standards language" that addresses functionality. At the same time, the committee realized its obligation to the end users to assure that requirements for safety, dependability, and maintenance are met, so details are often listed that were derived from many field implementations currently in use.

While the Committee also attempted to keep the language open enough for development of newer technology, because representation and input from any newer technologies was not received to date, the committee focused on existing technologies currently used. As new technologies emerge, this standard can still be used as a benchmark, whereby the developers of new technologies should be able to show either their compliance to the requirements of the standard, or how the newer technology exceeds the intent of this standard. Once a newer technology is tried, used and accepted by end users or other third party agencies, representatives of newer technology should participate in future revisions and versions of this standard through the NEMA standards development process.