

American National Standard for Electricity Meters— 0.1, 0.2, and 0.5 Accuracy Classes

NOTICE OF ADOPTION

ANSI C12.20 was adopted and is approved for use by the Department of Defense (DoD). The National Electrical Manufacturers Association has furnished the clearance required by existing regulations. Copies of the document are stocked at the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, for issue to DoD activities only. All other requestors must obtain copies from NEMA. ANSI C12.20 was adopted by the Dominica Bureau of Standards and is approved for use by the Commonwealth of Dominica.

Secretariat:

National Electrical Manufacturers Association

Approved: February 17, 2017

American National Standards Institute, Inc.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

ANSI standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process to promote fairness in the development of consensus, it does not write the document, and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by The American National Standards Institute, Inc. (ANSI) that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer. An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly, and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made toward their resolution.

The existence of an American National Standard does not in any respect preclude anyone, whether s/he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards. It is intended as a guide to aid the manufacturer, the consumer, and the general public.

The American National Standards Institute, Inc., does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute, Inc. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on this title page.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute, Inc. require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, Inc.

Published by

National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

© 2017 National Electrical Manufacturers Association

All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

Foreword (This foreword is not part of American National Standard C12.20)

This American National Standard establishes acceptable performance criteria for electricity meters. Accuracy class designations, current class designations, voltage and frequency ratings, test current values, service connection arrangements, pertinent dimensions, form designations, and environmental tests are covered.

The existing C12.20 standard has been revised with the intent to bring it up to date in an industry that is changing dramatically because of both technology and regulatory matters.

Major changes in this edition include testing under harmonic conditions, addition of a 0.1% accuracy class, clarification that non-Blondel applications are not covered by this standard, and addition of specifications for the optical test output port.

In memoriam to Herman Millican: Herman had a passion for standards and members of SC16 felt fortunate to know and learn from him.

Suggestions for improvement to this standard are welcome. They should be sent to:

National Electrical Manufacturers Association Senior Technical Director 1300 North 17th Street Suite 900 Rosslyn, VA 22209

This standard was processed and approved for submittal to ANSI by Accredited Standards Committee for Electricity Metering, C12. At the time the committee approved this standard, the C12 Main Committee had the following members:

Shannon Edwards, Chairperson ANSI C12/SC16 Tom Nelson, Chairperson ANSI C12 Paul Orr, Secretary

Organization Represented	Name of Representative	Organization Represented	Name of Representative
General Interest Elevate Energy	L. Kotewa	NIST	T. Nelson
ERCOT	D. Tucker	Power Measurements, LLC	W. Hardy
EnerNex LLC	A. Snyder	Tucker Engineering	R. Tucker
Future DOS R&D Inc.	A. Moise	UL, LLC.	S. Hunter
MET Laboratories, Inc.	J. Reed		
<u>Producer</u>			
Elster Electricity	S. Weikel	Schweitzer Engineering Laboratories	T. Mooney
Aclara	C. Crittenden	Sensus Metering	K. O'Dell
Itron Inc.	B. Cain	Silver Springs Networks	K. Oza
Landis+Gyr Inc.	J. Voisine	Technology for Energy Corp	S. Hudson
Milbank Manufacturing Co.	S. Glasgow	TESCO	T. Lawton
Radian Research, Inc. Schneider Electric	S. Edwards	Watthour Engineering Co.	L. Wren
Scrineider Electric	S. Pedro		

D. Rhoades	Florida Power & Light	J. DeMars
J. Thurber	Oncor Electric Delivery Co. LLC	B. Johnson
D. Jirikovic	Pacific Gas & Electric	D. Y. Nguyen
K. Tolios	Public Service Electric & Gas	D. Ellis
T. Morgan	Xcel Energy	D. Nordell
G. Belcher		
	J. Thurber D. Jirikovic K. Tolios T. Morgan	J. Thurber Oncor Electric Delivery Co. LLC D. Jirikovic Pacific Gas & Electric K. Tolios Public Service Electric & Gas T. Morgan Xcel Energy

ANSI C12 C12.16 Subcommittee Members

Shannon Edwards, Chair Radian Research, Inc.
William Hardy, Vice-Chair Power Measurements, LLC

Organization Represented	Name of Representative	Organization Represented	Name of Representative
Alabama Power Company	D. Rhoades	NIST	T. Nelson
Baltimore Gas & Electric	J. Thurber	NIST	A. Thompson
Consumers Energy	D. Jirikovic	Oncor Electric Delivery Co., LLC	B. Johnson
DTE Energy	K. Tolios	Pacific Gas & Electric	D. Y. Nguyen
Duke Energy	T. Morgan	Power Measurements, LLC	W. Hardy
ERCOT	D. Tucker	Public Service Electric & Gas	D. Ellis
Elevate Energy	L. Kotewa	Radian Research Inc.	S. Edwards
Elster Solutions	S. Weikel	Schneider Electric	S. Pedro
EnerNex LLC	A. Snyder	Schweitzer Engineering Lab	T. Mooney
Eversource Energy	G. Belcher	Technology for Energy Corp.	S. Hudson
Florida Power & Light	J. DeMars	TESCO	T. Lawton
Future DOS R&D Inc.	A. Moise	UL, LLC	S. Hunter
Aclara	C. Crittenden	Watthour Engineering Co.	L. Wren
Itron, Inc.	B. Cain	Xcel Energy EMC	D. Nordell
Landis+Gyr	J. Voisine	Landis+Gyr	F. Boudreau
MET Laboratories, Inc.	J. Reed		

In addition, the following representatives comprised the Editorial Committee for the current revision of C12.20:

Organization Represented Name of Representative

Power Measurements, LLC	W. Hardy (Chair)
Eversource Energy	G. Belcher
Ametek Power Instruments	S. Bleier
Radian Research Inc.	S. Edwards
Aclara	M. Hoffman
Technology for Energy Corp.	S. Hudson
Oncor Electric Delivery Co. LLC	B. Johnson
Schweitzer Engineering Laboratories	T. Mooney
Xcel Energy	D. Nordell
Schneider Electric	S. Pedro
MET Laboratories, Inc	J. Reed
Electric Reliability Council of Texas	D. Tucker

< This page intentionally left blank. >

CONTENTS

го 1			
	•		
2		ns	
3	Reference	es	1
4	Requirer	nents	1
	4.1 Moui	nting	1
		ige and Frequency	
		ent classes and test amperes	
		designations	
4		ays	
		Viewing requirements	
		Size of digits	
		Direction of energy flow	
•		isions for testing of calibration	
		Requirement for test outputs	
		Physical implementation of test pulse output	
		eplate	
		Nameplate additions	
		Nameplate deletions	
5		ble Performance Of New Types Of Electricity Metering Devices And Associa	
		Die Performance Of New Types Of Electricity Metering Devices And Associa	
,		eral	
		Acceptable meters	
		ction of metering devices for approval testslitions of test	
		s governing the acceptance of types	
		ormance requirements	
		Test conditions	
	5.5.2	Loading for accuracy tests	6
		List of type tests	
		Accuracy tests	
	5.5.4.1		
	5.5.4.2		
	5.5.4.3 5.5.4.4	· ·	
	5.5.4.4	Test Number 5: Effect of variation of voltage	
	5.5.4.6	Test Number 6: Effect of variation of frequency	
	5.5.4.7		
	5.5.4.8	Test Number 8: Internal meter losses	
	5.5.4.9	Test Number 9: Temperature rise	15
	5.5.4.1		
	5.5.4.1		
	5.5.4.1		
	5.5.4.1	, ,	
	5.5.4.1 5.5.5	4 Test Number 14: Effect of polyphase loading External influences	
	5.5.5.1	Performance verification	
	5.5.5.2	Test Number 15: Insulation	
	5.5.5.3	Test Number 16: Voltage interruptions test	
	5.5.5.4	Test Number 17: Effect of high voltage line surges	
	5.5.5.5		

	5.5.5.6	Test Number 19: Effect of variation of ambient temperature	
	5.5.5.7	Test Number 20: Effect of temporary overloads	20
	5.5.5.8	Test Number 21: Effect of current surge in ground conductor	20
	5.5.5.9	Test Number 22: Effect of superimposed signals	
	5.5.5.10	Test Number 23: Effect of voltage variation-secondary time base	
	5.5.5.11	Test Number 24: Effect of variation of ambient temperature-secondary time base	
	5.5.5.12	Test Number 25: Effect of electrical fast transient/burst test	
	5.5.5.13	Test Number 25a: Effect of electrical oscillatory SWC test	
	5.5.5.14	Test Number 26: Effect of radio frequency interference	
	5.5.5.15	Test Number 27: Radio frequency conducted and radiated emission test	
	5.5.5.16	Test Number 28: Effect of electrostatic discharge (ESD)	
	5.5.5.17	Test Number 29: Effect of storage temperature	
	5.5.5.18	Test Number 30: Effect of operating temperature	
	5.5.5.19	Test Number 31: Effect of relative humidity	
	5.5.5.20	Test Number 32: Mechanical shock	
	5.5.5.21	Test Number 33: Transportation drop	
	5.5.5.22	Test Number 34: Mechanical vibration	
	5.5.5.23	Test Number 35: Transportation vibration	
	5.5.5.24	Test Number 36: Weather simulation test	
	5.5.5.25 5.5.5.26	Test Number 37: Salt-spray test Test Number 38: Raintightness	
		rmonics influence: Effect of non-sinusoidal waveforms	
	5.5.6.1	Test Number 39: 90 Degree phase fired waveform	
	5.5.6.2	Test Number 40: Quadriform waveform	
	5.5.6.3	Test Number 41: Peaked waveform	
	5.5.6.4	Test Number 42: Pulse waveform	
	5.5.6.5	Test Number 43: Multiple zero crossings on current	
	5.5.6.6	Test Number 44: Multiple zero crossings on voltage	
_		·	
6		for in—Service Performance	
7	Requireme	nts Applicable to Detachable Watthour Meters	31
8	Requireme	nts Applicable to Bottom—Connected Electricity Meters	31
9	Procedure	for Assigning Form Designations	31
		Historical Background	
	A.1 Fore	word to Third Edition (2010)	32
		word to Second Edition (2002)	
		word to First Edition (1998)	
		90 Degree Phase Fired Waveform Definitions	
	Appendix C:	Type B Optical Test Output Port (OTOP)	40

1 Scope

This standard establishes the physical aspects and acceptable performance criteria for 0.1, 0.2, and 0.5 accuracy class electricity meters meeting Blondel's Theorem. Where differences exist between the requirements of this standard and the most current version of ANSI C12.1 and ANSI C12.10, the requirements of this standard shall prevail.