



ANSI Z535.1-2022

American National Standard for Safety Colors

Secretariat:

National Electrical Manufacturers Association

Approved: June 2, 2022

American National Standards Institute, Inc.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

ANSI standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process to promote fairness in the development of consensus, it does not write the document, and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by The American National Standards Institute, Inc. (ANSI) that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer. An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly, and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made toward their resolution.

The existence of an American National Standard does not in any respect preclude anyone, whether s/he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards. It is intended as a guide to aid the manufacturer, the consumer, and the general public.

The American National Standards Institute, Inc., does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute, Inc. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on this title page.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute, Inc. require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, Inc.

Published by

**National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209**

© 2022 National Electrical Manufacturers Association

All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

< This page is intentionally left blank. >

CONTENTS

Foreword v

1 Introduction 1

2 Scope and Purpose..... 1

 2.1 Scope 1

 2.2.1 Existing Standards and Regulations 1

3 Application and Exceptions 1

 3.1 Applications 1

 3.2 Exceptions 2

4 Explanation of Terminology 2

5 Specifications 3

 5.1 General 3

 5.2 Testing Specifications 3

6 Safety Colors..... 3

 6.1 Safety Colors Ordinary Surface Colors 3

 6.2 Safety White 4

 6.3 Safety Black 4

 6.4 Daylight Fluorescent Safety Colors..... 4

7 Optimum Visibility..... 4

8 Surface Finish 4

9 External Illumination of Safety Colors 5

10 Safety Color Stability 5

11 Normative References 5

Annex A..... 17

Annex B..... 18

Annex C..... 19

Annex D..... 21

Annex E..... 24

Annex F Informative References 26

2027 Revisions..... 27

Form for Proposals..... 28

Figures

Figure 1	Section of the CIE 1931 Chromaticity Diagram Showing Green, Yellow-to-Red Region, and Chromaticity Specification Boundaries for ANSI Z535.1 Fluorescent Safety Colors	13
Figure 2	CIE 1931 Chromaticity Diagram Color Regions for ANSI Z535.1 <i>Safety Colors</i>	14
Figure 3	Enlarged View of the CIE 1931 Chromaticity Diagram Showing Neutral Limits for Safety White and Safety Black	15
Figure A-1	Enlarged View of the CIE 1931 Chromaticity Diagram Showing the Color Region for Safety Yellow	17
Figure B-1	ANSI Z535.1 <i>Safety Colors</i> Using Illuminant C, and ISO 3864-4 Safety Colors Using Standard Illuminant D65	18
Figure E-1	Munsell Hue Circle	24
Figure E-2	Munsell Hue, Value, and Chroma for Safety Red	25

Tables

Table 1	(Appendix A to §172—Office of Hazardous Materials Transportation Color Tolerance Charts and Tables) Specifications for Color Tolerance Charts for Use with Labels and Placards Surfaced with Paint, Lacquer, Enamel, Plastic, Other Opaque Coatings, or Ink	7
Table 2	Specifications for Color Tolerance Charts for Use with Labels and Placards Surfaced with Ink	8
Table 3	Specification for Colors for Use with Labels Printed on Packaging Surfaces	11
Table 4	Specification for Fluorescent Safety Colors Recommended Limits of Fluorescent Colors in Terms of CIE Recommendations No. 39-2, 1983 for Surface Colors for Visual Signaling	11
Table 5	(<i>x</i> , <i>y</i>) Chromaticity Coordinates of the Corners of the Recommended Limits for Fluorescent Safety Colors Specified in Table 4, in Terms of the CIE 1931 Standard Colorimetric System, Measured with 45/0 Geometry, and Evaluation with CIE Standard Illuminant D65	12
Table 6	Specifications for Safety White and Safety Black	16
Table C-1	ANSI Z535.1 <i>Safety Colors</i> —Cross-Reference Table	19
Table D-1	Ordinary Materials: Examples for Object Colors That Fall Within the Specified Chromaticity Coordinates and Luminance Factor for the Color Region	21
Table D-2	ISO References for Color Order Systems for Safety Color Orange	23

< This page is intentionally left blank. >

Foreword

In 1979, the ANSI Z53 Committee on Safety Colors was combined with the ANSI Z35 Committee on Safety Signs to form the ANSI Z535 Committee on Safety Signs and Colors. The Z535 Committee has the following scope:

To develop standards for the design, application, and use of signs, colors, and symbols intended to identify and warn against specific hazards and for other accident prevention purposes.

While the basic mission and fundamental purpose of the ANSI Z535 Committee is to develop, refine, and promote a single, uniform graphic system used for communicating safety and accident prevention information, the Z535 Committee recognizes that this information can also be effectively communicated using other graphic systems.

The Z535 Committee created subcommittees to update the Z53 and Z35 standards and to write new standards. To date, the following six standards make up the ANSI Z535 series:

- ANSI Z535.1 *Safety Colors* [ANSI Z53.1-1979 was updated and combined with this standard in 1991]
- ANSI Z535.2 *Environmental and Facility Safety Signs* [ANSI Z35.1-1972 and Z35.4-1972 were updated and combined into this standard in 1991]
- ANSI Z535.3 *Criteria for Safety Symbols* [new in 1991]
- ANSI Z535.4 *Product Safety Signs and Labels* [new in 1991]
- ANSI Z535.5 *Safety Tags and Barricade Tapes (for Temporary Hazards)* [ANSI Z35.2-1974 was updated and combined with this standard in 1991]
- ANSI Z535.6 *Product Safety Information in Product Manuals, Instructions, and Other Collateral Materials* [new in 2006]

Together, these six standards contain the information needed to specify formats, colors, and symbols for safety signs used in environmental and facility applications, product and product literature applications, and temporary safety tag and barricade tape applications.

Published separately is the ANSI Z535 Safety Color Chart. This chart gives the user a sample of each of the safety colors red, orange, yellow, green, blue, purple, white, and black. It also describes each color's ink formulation and closest PANTONE® color.

This ANSI Z535.1 standard was prepared by the Z535.1 Subcommittee on Safety Colors. The foreword and all annexes are considered to be informative; the body is considered normative. In the vocabulary of writing standards, the word "informative" is meant to convey that the content presented is for informational purposes only and is not considered to be mandatory in nature. The word "normative" is meant to convey that the content is considered to be mandatory or prescriptive.

The 2022 edition of this standard is the tenth revision of the American War Standard, developed at the request of the War Department and approved by the American Standards Association (ASA) on July 16, 1945. The ASA was reconstituted as the USA Standards Institute (USASI) in August 1966, and as the American National Standards Institute (ANSI) in October 1969. Peacetime work on revising the American War Standard containing the Safety Color Code began in 1946 under committee procedures of the ASA, with the National Safety Council serving as a sponsor of the project. The Sectional Committee on the Safety Color Code, Z53, reviewed the War Standard and enlarged its application to include the colors orange, blue, and purple. The committee also approved standard definitions and limits for the colors. The revised standard was approved by the ASA on September 11, 1953. In the 1971 revision, the Z53 committee deleted the color blue and modified the application of the color yellow because of conflicts with other American National Standards.

In the fourth revision, a significant step forward was made toward increased safety through uniformity in safety color coding. The safety colors formerly used in this standard were combined and adjusted to give the best feasible discrimination for observers with either normal or color-deficient (colorblind) vision. For the first time, safety color tolerance charts were available for use with this standard (see Section 8, Reference 17). Each color tolerance chart shows the standard color and six color tolerances, illustrating acceptable ranges in hue, value (lightness), and chroma (saturation). Each color tolerance chart also lists the Munsell Notation and equivalent Commission Internationale de L'Eclairage (CIE) specifications (x, y, Y) for each standard color and tolerance sample. The colors brown, blue, and gray were added, and Table 1 was expanded to include the same information on most of the levels of the Universal Color Language (UCL) for the tolerance samples as for the standard or central sample of each Safety Color. Sections 1 to 6 of the present standard contain material similar to the fourth revision (Z53.1, 1979).

The intent of the fifth revision (1991) of the safety color standard was to provide a series of visually distinguishable safety colors, each with specific uses.

The sixth revision in 1998 incorporated corrections and additions that helped to clarify the use of the standard in conjunction with the other Z535 standards. Annex A was also added at this time to explain how to relate the CIE safety color specifications contained in Table 1 with the CIE chromaticity diagrams illustrated in Figures 1, 2, and 3.

The seventh revision of the ANSI Z535.1 *Safety Color Code* in 2002 had two major changes. The first is the deletion of information concerning the application of the safety colors. The intention of making this change was to maintain Z535.1 as the standard that defines the safety colors in terms of their color tolerances. The *application* of the colors (i.e., how they are to be used) properly belongs to the other standards in the ANSI Z535 series as well as to other standards that include uses for safety colors. The second change was to include the "closest PANTONE color" number for all of the safety colors on the Safety Color Chart that did not have a PANTONE color reference. This was a practical addition that makes it easier for those needing to specify a safety color using the PANTONE color matching system.

It is important to note that the color-rendering characteristics of several types of modern, high-efficiency light sources differ markedly from those of the average daylight source (CIE Source C) specified in Table 1. It is essential that candidate safety colors be examined under the actual light sources that will be used. This will ensure that they can be suitably differentiated and individually identified with their assigned color names.

The limited color gamut and aging characteristics of fluorescent colorants combine to restrict the number and chromaticities of fluorescent safety colors. For this reason, categories of unrestricted red-orange and unrestricted yellow fluorescent colors were added in 1998 to supplement the restricted specifications that are equivalent to CIE international standards. The unrestricted specifications may be used when no more than three distinguishable fluorescent safety colors are required for outdoor use for up to two years.

Recent research is providing conclusive evidence that highly chromatic colors, in some chromaticities, serve to increase or decrease the perception of lightness (for reflective materials) and brightness (for self-luminous objects). The effect is more dramatic in the case of colored lights and colored retroreflective materials. Future revisions of this standard might consider opportunities for improving the visibility of safety signs, colors, and symbols through the selective use of vividly colored retroreflectors, as well as include test methods and color specifications for retroreflective and self-luminous materials.

The 2006 version of this standard was nearly identical to the ANSI Z535.1-2002 version, with an updated reference section and a new title, reflecting that the standard is meant to be used as a reference to define specific colors, not to set forth or codify the uses of these colors for specific purposes.

In 2010, the Z535.1 Subcommittee reviewed ANSI Z535.1-2006 and, not identifying any technical changes, recommended reaffirmation of the standard to the Z535 Committee. In its review, however, the Z535.1 Subcommittee made the following corrections:

- a. In Table 1, corrected the following for Safety Orange:
 1. Value + changed from 5.0YR 6.0/15 to 5.0YR 6.5/15
 2. Value – changed from 5.0YR 6.5/15 to 5.0YR 5.5/15
 3. Chroma + changed from 5.0YR 5.5/15 to 5.0YR 6.0/16
- b. In Annex A, 6th paragraph, after “CIE 1931,” replaced the box symbol with a degree symbol
- c. In Figure 1, the centroid for each color was checked and relocated as necessary

In 2012, the Z535.1 Safety Colors Subcommittee recommended that the entire standard be revised. The following updates were included in the 2017 edition of the standard. References to hazardous materials labels and placard color tolerance charts were minimized because of their limited availability. These charts are no longer being produced or offered for sale, but are on display in the Office of Hazardous Materials Safety, Office of Hazardous Materials Standards, Washington, D.C.

ANSI Z535.1 *Safety Colors* harmonized with the Code of Federal Regulations, Title 49 Transportation, §172.407, Labeling Specifications. Tables 1, 2, and 3, Appendix A, replaced Table 1 in the Z535.1 standard. Tables 2 and 3 allow for differences in production methods and will help to ensure safety colors remain within their recommended tolerances. The Munsell Notations and chromaticity coordinates are identical in both the CFR Table 1 and ANSI Z535.1; the exception is how color is described. The new Table 1 is now more accessible to those unfamiliar with the Munsell Color System. An adjustment was made to the new Table 1 to include the original Munsell description of hue, value, and chroma in the Munsell Notation column.

The normative body of the standard was simplified and designed as a tool for specifying safety colors consistently. Definitions of terms were included, so readers have a basic understanding of references made within the standard. More emphasis was placed on what can affect a safety color’s appearance and cause it to fall outside the acceptable tolerance limits rather than the technical measurement of safety colors, which is beyond the scope of this standard. Fluorescent safety color information was updated and expanded.

Realizing the need to make this standard more user-friendly and easy to understand, several new Annexes were added. Annex A clarifies the color boundaries for Safety Yellow. Annex B illustrates ANSI safety color boundaries and ISO safety color boundaries together on a chromaticity diagram so one can see where ANSI safety colors plot in comparison to ISO safety colors. Annex C contains color cross-reference tables that include the Munsell Notation, a PANTONE number, C-M-Y-K percentages, and an RGB formula for each ANSI and ISO safety color. Annex D was added, and ISO safety colors and contrast colors of ordinary materials are shown in Table D-1. Annex E illustrates the Munsell Hue Circle and provides a visual detail of Hue, Value, and Chroma.

Safety Gray and Safety Brown were eliminated from Table 1. These colors are in use by other signage systems but are not considered hazard alerting colors for accident prevention. The PANTONE colors originally specified in 2002 for the Safety Color Chart were changed to harmonize with the PANTONE colors specified in the Code of Federal Regulations, Title 49 Transportation, §172.407, section 5.

The following color standards in the PANTONE formula guide coated/uncoated may be used to achieve the required ANSI safety colors on markings and hazard warning labels and placards; see Table C-1.

For Red:	Use PANTONE 186 C
For Orange:	Use PANTONE 151 C
For Yellow:	Use PANTONE 109 C
For Green:	Use PANTONE 335 C
For Blue:	Use PANTONE 285 C
For Purple:	Use PANTONE 259 C

The original PANTONE colors referenced on the 2011 Safety Color Chart are acceptable for use, as these colors are within safety color tolerances given in Table 1. Specification of the PANTONE colors listed here will be encouraged, as they will replace the original PANTONE colors on the 2011 Safety Color Chart.

For compliance with ISO Safety Colors, see Annex C, Table C-2, and Table D-1. ISO safety colors fall within ANSI Z535.1 safety color tolerance boundaries as defined in Table 1 of this standard.

The 2022 edition of this standard incorporates minor updates for consistency with the other ANSI Z535 standards. The 2022 edition of this standard was revised to clarify the relationship between this standard and other applicable standards and regulations.

Proposals for the improvement of this standard are welcome. Information concerning the submittal of proposals to the ANSI Z535 Committee for consideration can be found at the back of this standard.

This standard was processed and approved for submittal to ANSI by the Accredited Standards Committee Z535 on Safety Signs and Colors. Committee approval of this standard does not necessarily imply that all committee members voted for its approval. At the time of approval, the Z535 Committee had the following members:

Steve Hall, Chair

Judith J. Isaacson, Vice Chair

Paul Orr, Secretary

<i>Organization Represented:</i>	<i>Name of Representative:</i>
<i>Alamo Group (USA) Inc.</i>	<i>Brett Cohen Sam Gallegos (Alt.)</i>
<i>American Society of Safety Professionals</i>	<i>J. Paul Frantz Thomas F. Bresnahan (Alt.) Timothy Rhoades (Alt.)</i>
<i>American Welding Society</i>	<i>August F. Manz</i>
<i>Applied Materials</i>	<i>Edward Karl Edwin Palmero (Alt.)</i>
<i>Applied Safety and Ergonomics</i>	<i>Steve Hall Judith J. Isaacson (Alt.)</i>
<i>Association of Equipment Manufacturers</i>	<i>Valerie Lynch</i>
<i>B11 Standards, Inc.</i>	<i>David Felinski</i>
<i>Bell Product Safety</i>	<i>Gary Bell</i>
<i>Browning Arms Company</i>	<i>Larry D. Nelson</i>
<i>BRP</i>	<i>Marc Larouche Karl Richard (Alt.)</i>
<i>Caterpillar, Inc.</i>	<i>Charles Crowell Justin Rose (Alt.)</i>
<i>Clarion Safety Systems, LLC</i>	<i>Angela Lambert Geoffrey Peckham (Alt.)</i>
<i>Corelle Brands</i>	<i>Jennifer Pritchard</i>

<i>Dorris and Associates International, LLC</i>	<i>Nathan T. Dorris Eric Boelhouwer (Alt.)</i>
<i>Eagle Crusher Co.</i>	<i>Ryan Parsell</i>
<i>Graco Inc.</i>	<i>Angela Redlund-Spieker</i>
<i>Human Factors & Ergonomics Society</i>	<i>Michael Kalsher William J. Vigilante Jr. (Alt.)</i>
<i>Human Factors & Safety Analytics, Inc.</i>	<i>B. Jay Martin</i>
<i>International Safety Equipment Association</i>	<i>Cristine Fargo</i>
<i>International Staple, Nail, and Tool Association</i>	<i>Rick Allen Stephanie Thompson (Alt.)</i>
<i>Kunding Consulting</i>	<i>Mathew Kunding</i>
<i>National Electrical Manufacturers Association</i>	<i>Bill Pratt David Werba (Alt.)</i>
<i>Nutron/GPI Association</i>	<i>Russ Butchko</i>
<i>Polyfuze</i>	<i>Matthew Stevenson Marty Mares (Alt.)</i>
<i>Power Tool Institute</i>	<i>Drew Hornick Mark Hickok (Alt.)</i>
<i>Rockwell Automation</i>	<i>Steven Chybowski</i>
<i>Safety & Forensic Enterprises, LLC</i>	<i>Loren Mills</i>
<i>Snap-on Tools</i>	<i>Dan Eggert</i>
<i>Taylor Communications</i>	<i>Jody Dombeck Linda LeBlanc (Alt.)</i>
<i>Travelers Insurance Company</i>	<i>David Roy Joe Bailey (Alt.)</i>
<i>Underwriters Laboratories, Inc.</i>	<i>Richard Olesen</i>
<i>USDA Rural Development Utilities</i>	<i>Trung Hiu</i>

At the time it prepared this standard for the Z535 Committee vote, Subcommittee Z535.1 on Safety Colors had the following members:

Angela Lambert, Chair

Paul Orr, Secretary

Jody Dombeck, Taylor Communications

Judith J. Isaacson, Applied Safety and Ergonomics

Michael Kalsher, Human Factors & Ergonomics Society

1 Introduction

Safety colors are often used to supplement a word message or safety symbol. The standardization of safety colors assists with the efficient development of safety information and assists viewers in recognizing information as being related to safety.

This standard provides specifications for producing consistent safety colors. The safety colors specified in ANSI Z535.1 *Safety Colors* are used by:

ANSI Z535.2 *Environmental and Facility Safety Signs*

ANSI Z535.3 *Criteria for Safety Symbols*

ANSI Z535.4 *Product Safety Signs and Labels*

ANSI Z535.5 *Accident Prevention Tags (for Temporary Hazards)*

ANSI Z535.6 *Product Safety Information in Product Manuals, Instructions, and Other Collateral Materials*

2 Scope and Purpose

2.1 Scope

This standard provides a system for specifying safety colors, in terms of Munsell Notations, CIE colorimetric data, defined chromaticity regions, and color formulas for each ANSI and ISO safety color used on safety signs, labels, and tags. It is beyond the scope of this standard to provide in-depth instructions for color measurement. It is beyond the scope of this standard to address the color of safety sign, label, or tag substrates.

2.2 Purpose

The purpose of this standard is to:

- a. implement a uniform system for specifying safety colors;
- b. include safety color formulas for a variety of applications and media for specifying ANSI and ISO Safety Colors (Annex C);
- c. harmonize with safety colors specified in the Code of Federal Regulations, 49 CFR, §172.407 (Subpart E)(Tables 1-3), 49 CFR, §172.407 Label Specifications (5); and
- d. harmonize with ISO 3864-4 *Graphical symbols—Safety colours and safety signs—Part 4: Colorimetric and photometric properties of safety sign materials* (Annex D). These colors are specified in order to facilitate compliance with ISO safety colors.