

Approved as an American National Standard ANSI Approval Date: September 20, 2018

ANSI/NEMA Standards Publication WC 76-2018

Standard for Controlled Impedance Shielded Twisted Pairs
In Internal Electrical Cable

Published by:

National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

www.nema.org

© 2018 National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

American National Standards Institute (ANSI) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety–related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

Foreword

In the preparation of this Standards Publication, input of users and other interested parties has been sought and evaluated. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product Subdivision by contacting the:

Technical Director, Operations National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

Section approval of the standard does not necessarily imply that all section members voted for its approval or participated in its development. At the time it was approved, the Section was composed of the following members:

Atkore International Cable USA LLC

Champlain Cable Corporation

Comtran Cable LLC Freeport-McMoRan

General Cable a company of the Prysmian Group

Marine Tech Wire and Cable, Inc. Monroe Cable Company, Inc., The

New England Wire Technologies Corporation

Nexans

Quirk Wire Company, Inc.

Radix Wire

RSCC Wire & Cable Group Rubadue Wire Co., Inc. SEA Wire and Cable, Inc. Southwire Company TE Connectivity The Okonite Company

Virginia Insulated Products, Inc.

WireMasters, Inc.

Harvey, IL Naples, FL Colchester, VT Attleboro, MA Phoenix, AZ

Highland Heights, KY

York, PA Middletown, NY Lisbon, NH Markham, ON West Brookfield, MA Euclid, OH East Granby, CT Loveland, CO Madison, AL

Ramsey, NJ Saltville, VA Columbia, TN

Carrollton, GA

Harrisburg, PA

CONTENTS

Section 1	General	
	1.1 Scope	1
	1.2 Reference Standards	1
	Order of Precedence	
Section 2 Classification		3
	2.1 General	3
	2.2 Cable Designation	
	2.2.1 Characteristic Impedance	
	2.2.2 Conductor Material and Stranding	
	2.2.3 Conductor Size	
	2.2.4 Dielectric and Component Shield Covering Type	
	2.2.5 Component Identification	
	2.2.6 Number of Components	
	2.2.7 Component Shield Material	
	2.2.8 Overall Shield Material	
	2.2.9 Jacket Material	
Section 3	Requirements	10
	3.1 Construction and Materials	
	3.2 Basic Wire	
	3.2.1 Extruded Polytetrafluoroethylene (PTFE) (Type EE)	
	3.2.2 Extruded Fluorinated Ethylene Propylene (FEP) (Type KK)	
	3.2.3 Extruded, Foamed Fluorinated Ethylene Propylene (FEP) (Type KF)	10
	3.2.4 Extruded Cross-linked Polyethylene (TYPE LL)	
	3.2.5 Extruded Ethylene Tetra-Fluoroethylene (ETFE) (Type TZ)	
	3.2.6 Extruded Cross-linked Ethylene Tetra-Fluoroethylene (XLETFE) (Type XE)	
	3.2.7 Extruded Cross-linked Low Smoke Zero Halogen Polyolefin (XLPO)(Type ZH)	11
	3.3 Cabling	
	3.3.1 Direction of Lay	13
	3.3.2 Length of Lay	
	3.4 Fillers and Tapes	13
	3.5 Component and Overall Shields	
	3.5.1 Silver-Coated Copper Strands	
	3.5.2 Nickel-Coated Copper Strands	
	3.5.3 Tin-Coated Copper Strands	
	3.5.4 Shield Strand Size	
	3.5.5 Braid Angle	
	3.5.6 Shield Coverage	
	3.5.7 Shield Splices	
	3.5.8 Foil Shields	
	3.6 Overall Jacket	
	3.6.1 Jacket Concentricity	
	3.6.2 Jacket Color	
	3.6.3 Jacket Strippability	
	3.6.4 Jacket Materials	
	3.6.5 Jacket Wall Thickness	
	3.7 Performance	
	3.7.1 Dielectric Strength	
	3.7.2 Conductor Continuity	
	3.7.3 Component Wire	
	3.7.5 Heat Resistance	
	0.7.0 Float (16313ta) (165	10

3.7.6 Flame Propagation	19
3.7.7 Crosslinked Verification	19
3.7.8 Acid Gas Generation	19
3.7.9 Halogen Content	19
3.7.10 Smoke Index	19
3.7.11 Toxicity Index	19
3.7.12 Characteristic Impedance	19
3.7.13 Impedance	20
3.7.14 Capacitance	20
3.7.15 Surface Transfer Impedance	20
3.7.16 Minimum Bend Radius	
3.8 Workmanship	
Section 4 Verification	
4.1 Classification of Inspections	
4.2 Inspection Conditions	
4.3 First Article Inspection	
4.4 Conformance Inspection.	
4.4.1 Specimen Length	
4.4.2 Failures	
4.4.3 Inspection Lot	
4.4.4 Group A, B, and C Inspection	
4.4.5 Group D Inspection	
4.4.6 Sampling	
4.4.7 Rejected Lots	
4.4.8 Non-Compliance	
4.5 Methods of Inspection	
4.5.1 Dielectric Strength	
4.5.2 Jacket Flaws	
4.5.3 Conductor Continuity	
4.5.4 Component Wire	
4.5.5 Dielectric Immersion (Jacketed or Shielded and Jacketed Cable)	
4.5.6 Visual and Mechanical Inspection	
4.5.7 Shield Braid Angle and Coverage	
4.5.8 Jacket Concentricity	
4.5.9 Jacket Strippability	
4.5.10 Jacket Tensile Strength and Elongation	
4.5.11 Jacket Wall Thickness	24
4.5.12 Cold Bend	
4.5.13 Heat Resistance	
4.5.14 Flammability	
4.5.15 Cross-linked Verification of Jackets	
4.5.16 Acid Gas Generation	
4.5.17 Halogen Content	
4.5.18 Smoke Index	
4.5.19 Toxicity Index.	
•	
Section 5 Packaging	
5.1 General	
5.2 Continuous Lengths	
Section 6 Notes	
6.1 Intended Use	29
6.2 Acauisition Reauirements	29

<This page intentionally left blank.>

Section 1 General

1.1 Scope

This Standards Publication was developed to cover specific requirements for finished cables with controlled impedance shielded twisted pair(s). This standard uniquely enables a user to specify various numbers of shielded pairs (1–61) with a required impedance requirement, and tailor the materials to meet a specific end application. The cables are intended for wiring of electrical equipment.