

### **NOTICE AND DISCLAIMER**

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) Standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus Standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its Standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this Standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other Standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

## **CONTENTS**

Forewordxi			
Section I	General Standards Applying to All Machines Part 1 Referenced Standards and		
Definition	1S	1	
1.1	Scope		
1.2	Referenced Standards		
	itions		
	ification According to Size		
1.3	Machine		
1.4	Small (Fractional) Machine		
1.5	Medium (Integral) Machine		
1.6	Large Machine	5	
1.7	General-Purpose Motor	6	
1.8	Industrial Small Motor	6	
1.9	Definite-Purpose Motor	6	
1.10	Special-Purpose Motor		
	ification According to Electrical Type		
1.11	General		
	1.11.1 Electric Motor		
1.12	Electric Machines		
	1.12.1 Synchronous Motor		
	1.12.2 Permanent Magnet Synchronous Motor		
4.40	1.12.3 Line-Start Permanent Magnet Synchronous Motor (LSPM)	<u>7</u>	
1.13	Design Letters of Line-Start Permanent Magnet Synchronous Medium Motors		
	1.13.1 Design MA		
01	1.13.2 Design MB		
	ification According to Environmental Protection and Methods of Cooling		
1.14	Open Machine (IP00, IC01)		
	1.14.1 Drip-Proof Machine (IP12, IC01)	7	
	1.14.3 Semi-Guarded Machine (IC01)		
	1.14.4 Guarded Machine (IC01)		
	1.14.5 Drip-Proof Guarded Machine (ICO1)		
	1.14.6 Open Independently Ventilated Machine (IC06)	10	
	1.14.7 Open Pipe-Ventilated Machine	10	
1.15	Weather-Protected Machine		
	1.15.1 Type I (IC01)		
	1.15.2 Type II (IC01)		
1.16	Totally Enclosed Machine		
	1.16.1 Totally Enclosed Nonventilated Machine (IC410)		
	1.16.2 Totally Enclosed Fan-Cooled Machine	10	
	1.16.3 Totally Enclosed Fan-Cooled Guarded Machine (IC411)	11	
	1.16.4 Totally Enclosed Pipe-Ventilated Machine (IP44)	11	
	1.16.5 Totally Enclosed Water-Cooled Machine (IP54)	11	
	1.16.6 Water-Proof Machine (IP55)	11	
	1.16.7 Totally Enclosed Air-to-Water-Cooled Machine (IP54)	11	
	1.16.8 Totally Enclosed Air-to-Air-Cooled Machine (IP54)	11	
	1.16.9 Totally Enclosed Air-Over Machine (IP54, IC417)		
	1.16.10 Explosion-Proof Machine		
=	1.16.11 Dust-Ignition-Proof Machine		
1.17	Machine with Moisture-Resistant, Encapsulated, or Sealed Windings		
	1.17.1 Machine with Moisture-Resistant Windings	12	

	1.17.2 Machine with Encapsulated Windings	
	1.17.3 Machine with Sealed Windings	12
Classif	ication According to Variability of Speed	12
1.18	Constant-Speed Motor	
1.19	Adjustable-Speed Motor	
1.20	Base Speed of an Adjustable-Speed Motor	
	Performance, and Test	
1.21		
1.21	Rating of a Machine	
	1.21.1 Continuous Rating	
	1.21.2 Short-Time Rating	
1.22	Efficiency	
	1.22.1 General	13
1.23	Service Factor	13
1.24	EMF Definitions	13
	1.24.1 Back EMF	
	1.24.2 Voltage Constant	
1.25	Full-Load Torque	
1.26	Cogging Torque	
1.27	Torque Ripple	
1.28	Locked-Rotor Torque (Static Torque)	
1.29	Pull-up Torque	
1.30	Pull-out Torque	
1.31	Pull-in Torque	14
1.32	Locked-Rotor Current	14
1.33	No-Load Current	14
1.34	Demagnetization Current	14
1.35	Temperature Tests	
1.36	Ambient Temperature	
1.37	High-Potential Tests	
1.38	Radial Magnetic Pull and Axial Centering Force	
1.30		
	1.38.1 Radial Magnetic Pull	
	1.38.2 Axial Centering Force	
1.39	Equivalent Circuits	
	1.39.1 Polyphase Line-Start Permanent Magnet Machine	
	1.39.2 Polyphase Permanent Magnet Machine	15
	1.39.3 Definitions (See Figure 1-4)	15
1.40	Electromagnetic Compatibility (EMC)	17
	1.40.1 Electrical Noise	
1.41	Electrical Noise Immunity	
1.42	Electromagnetic Interference (EMI)	17
	ete Machines and Parts	
•		
1.43	Face- and Flange-Mounting	
	1.43.1 Type C Face	
	1.43.2 Type D Flange	
	1.43.3 Type P Flange	
	ication of Insulation Systems	
1.44	Insulation System	
	1.44.1 Coil Insulation with Its Accessories	17
	1.44.2 Connection and Winding Support Insulation	
	1.44.3 Associated Structural Parts	
1.45	Classification of Insulation Systems	
-	aneous	
1.46		
1.40	Nameplate Marking	
	1.46.1 Nameplate	
	1.46.2 Additional Nameplate Markings	19

	1.47	Code	Letter	19
	1.48	Therm	al Protector	19
	1.49		ally Protected	
	1.50		Femperature Protection	
	1.51		ant Flux	
	1.52		ion Factor	
	1.53	Markir	ng Abbreviations for Machines	20
			ls Applying to Polyphase Permanent Magnet Synchronous Alternating-Curren minal Markings	
	Genera	al		23
	2.1		on of Terminal Markings	
	2.2		nal Markings	
	2.3	Nume	rals on Terminals of Polyphase Permanent Magnet Synchronous Motors	
		2.3.1	Polyphase Permanent Magnet Synchronous Motors	
		2.3.2	· · · · · · · · · · · · · · · · · · ·	
		2.3.3		
		2.3.4		
			rmanent Magnet Synchronous Alternating-Current Motors	
	2.4		al Principles for Terminal Markings for Polyphase Permanent Magnet Synchronous	
			ating-Current Motors	
	0.5	2.4.1	Method of Marking	25
	2.5		nal Markings for Three-Phase Single-Speed Permanent Magnet Synchronous	26
			ating-Current Motors	
		2.5.1 2.5.2	Second	
		2.5.2	Third	
		2.5.4		
		2.5.5		
		2.5.6	Sixth	
	2.6		nal Markings for y- and Delta-Connected Dual-Voltage Motors	
			ices	
	2.7		nal Markings	
		2.7.1	General	
		2.7.2	Auxiliary Terminal Marking Rules	30
		2.7.3	Examples of Marking	31
		2.7.4	Auxiliary Devices within Motor	
		2.7.5	Auxiliary Devices External to Motor	
		2.7.6	Marking of Rigidly Mounted Terminals	
Ge	neral St	andard	s Applying to All Machines Part 3 Dimensions, Tolerances, and Mounting	35
	3.1		Symbols for Dimension Sheets	
	3.2		n for Designating Frames	
		3.2.1	Frame Numbers	44
		3.2.2	Frame Letters	
	3.3		Mounting and Terminal Housing Location	
	3.4	Dimen	sions—AC Machines	
		3.4.1	Dimensions for Alternating-Current Foot-Mounted Machines with Single Straight-Sl Extension	49
		3.4.2	Shaft Extensions and Key Dimensions for Alternating-Current Foot-Mounted Machi with Single Tapered or Double Straight/Tapered Shaft Extension	51
		3.4.3	Shaft Extension Diameters and Key Dimensions for Alternating-Current Motors Bui Frames Larger than the 449T Frame	53
		3.4.4	Dimensions for Type C Face-Mounted Foot or Footless Alternating-Current Motors	
		3.4.5	Dimensions for Type FC Face-Mounted for Accessories on End Opposite Drive End	
			Alternating-Current Motors	54

		3.4.6 Dimensions for Type D Flange-Mounted Footed or Footless Alternating-Current	
		Motors	
	3.5	Tolerance Limits in Dimensions.	
	3.6	Knockout and Clearance Hole Diameter for Machine Terminal Boxes	
	3.7	Tolerances on Shaft Extension Diameters and Keyseats	. 57
		3.7.1 Shaft Extension Diameter	
		3.7.2 Keyseat Width	
		3.7.3 Bottom of Keyseat to Shaft Surface	
		3.7.4 Parallelism of Keyseats to Shaft Centerline	
		3.7.5 Lateral Displacement of Keyseats	
		3.7.6 Diameters and Keyseat Dimensions	
		3.7.7 Shaft Runout	
		3.7.8 Shaft Extension Key(s)	. 61
	3.8	Ring Groove Shaft Keyseats for Vertical Shaft Motors	
	3.9	Method of Measurement of Shaft Runout and of Eccentricity and Face Runout of Mounting	
		Surfaces	. 61
		3.9.1 Shaft Runout	. 61
		3.9.2 Eccentricity and Face Runout of Mounting Surfaces	. 61
	3.10	Tolerances for Type C Face-Mounting and Type D Flange-Mounting Motors	
	3.11	Tolerances for Type P Flange-Mounted Motors	
	3.12	Mounting Bolts or Studs	
	3.13	Method to Check Coplanarity of Feet of Fully Assembled Motors	
	3.14	Method of Measurement of Shaft Extension Parallelism to Foot Plane	
	3.15	Measurement of Bearing Temperature	
	3.16	Terminal Connections for Small Motors	
		3.16.1 Terminal Leads	
		3.16.2 Blade Terminals	
	3.17	Motor Terminal Housings	
	• • • • • • • • • • • • • • • • • • • •	3.17.1 Small and Medium Motors	
		3.17.2 Dimensions	
Se	ction II (	General Standards Applying to Polyphase Permanent Magnet Synchronous Alternatin	
		otors Part 4 Mechanical Vibration—Measurement, Evaluation, and Limits	
	4.1	Scope	
	4.2	Object	
	4.3	References	
	4.4	Measurement Quantity	
	4.4	4.4.1 Bearing Housing Vibration	
		4.4.2 Relative Shaft Vibration	
	4.5	Measuring Equipment	
	4.6	Motor Mounting	
	4.0	4.6.1 General	
		4.6.2 Resilient Mounting/Free Suspension	
		·	
		4.6.3 Rigid Mounting	
	4.7	4.6.4 Active Environment Determination	
	4.7	Conditions of Measurement	
		4.7.1 Shaft Key	. /:
		4.7.2 Measurement Points for Vibration	
		4.7.3 Operating Conditions	
	4.0	4.7.4 Vibration Transducer Mounting	
	4.8	Limits of Bearing Housing Vibration	
		4.8.1 General	
	4.0	4.8.2 Axial Vibration	
	4.9	Limits of Relative Shaft Vibration	
		4.9.1 General	80

	4.9.2 Shaft Vibration Limits	80
General St	andards Applying to Polyphase Permanent Magnet Synchronous Alternating-C	urrent
	rt 5 Sound Power Limits and Measurement Procedures	
5.1	Scope	
5.2	General	
5.3	References	
5.4	Methods of Measurement	
5.5	Test Conditions	
5.5	5.5.1 Machine Mounting	
	5.5.2 Test Operating Conditions	
5.6	Sound Power Level	
5.7	Determination of Sound Pressure Level	
_	Small (Fractional) and Medium (Integral) Permanent Magnet Machines Part 6 Ra	
	and Medium Permanent Magnet Motors	
6.1	Scope	
6.2	Voltages	
6.3	Frequencies	
0.4	6.3.1 Alternating-Current Motors	
6.4	Horsepower and Speed Ratings	
	6.4.1 Small Permanent Magnet Motors	
	6.4.2 Polyphase Medium Permanent Magnet Motors	
6.5	Time Ratings for Polyphase Permanent Magnet Motors	
6.6	Code Letters (for Locked-Rotor kVA)	
	6.6.1 Nameplate Marking	
	6.6.2 Letter Designation	
	6.6.3 Single-Speed Motors	
	6.6.4 Broad- or Dual-Voltage Motors	
	6.6.5 Dual-Frequency Motors	
	6.6.6 Part-Winding-Start Motors	
6.7	Nameplate Temperature Ratings for Permanent Magnet Small Motors	
6.8	Nameplate Marking for Permanent Magnet Small Motors	
	6.8.1 Alternating-Current Polyphase Permanent Magnet Motors, Except Those Inc	luded in
	6.8.2 and 6.8.3	93
	6.8.2 Permanent Magnet Motors Rated Less than 1/20 Horsepower	93
	6.8.3 Motors Intended for Assembly in a Device Having Its Own Markings	
	6.8.4 Motors for Dual Voltage	
6.9	Nameplate Marking for Medium Polyphase Permanent Magnet Motors	
	6.9.1 Medium Polyphase Permanent Magnet Motors	
Small (Fra	ctional) and Medium (Integral) Motors Part 7 Tests and Performance	97
7.0	Scope	
7.0 7.1	High-Potential Test—Safety Precautions and Test Procedure	
7.2	High-Potential Test Voltages for Permanent Magnet Motors	
7.3	High-Potential Production Testing of Small Motors	
	7.3.1 Dielectric Test Equipment	98
7.4	7.3.2 Evaluation of Insulation Systems by a Dielectric Test	
7.4	Repetitive Surge Test for Small and Medium Motors	
7.5	Mechanical Vibration	
7.6	Bearing Losses—Vertical Pump Motors	
7.7	Test Methods	
7.8	Performance Characteristics	
7.9	Locked-Rotor Current of Three-Phase Small and Medium Motors	
	7.9.1 60 Hertz Design MB Motors at 230 Volts	
	7.9.2 50 Hertz Design MB Motors at 380 Volts	
7.10	Instantaneous Peak Value of Inrush Current	102

7.11	Locked-Rotor Torque of Single-Speed Polyphase Small and Medium Motors with Continuous Ratings		
7.12	Pull-in Torque of Single-Speed Polyphase Small and Medium Motors with Continuous	102	
1.12	Ratings	100	
7.13	Accelerating Torque of Single-Speed Polyphase Small and Medium Motors with Continuous	102	
1.13	Potings	งกว สกว	
7.14	RatingsPull-out Torque of Single-Speed Polyphase Medium Motors with Continuous Ratings	102	
7.14	Temperature Rise		
7.15	7.15.1 Small Motors—Motor Nameplates Marked with Insulation System Designation an		
	Ambient Temperature		
	7.15.2 Medium Polyphase Motors		
	7.15.3 Temperature Rise for Ambients Higher than 40 C		
	Below 0°C*		
7.16	Variation from Rated Voltage and Rated Frequency		
	7.16.1 Running		
	7.16.2 Starting		
7.17	Voltage Unbalance		
7.18	Variation from Rated Speed		
7.19	Nameplate Amperes—Medium Motors		
7.20	Occasional Excess Current		
7.21	Stall Time		
7.22	Performance of Small and Medium Polyphase Motors with Single, Dual, or Broad Range		
	Voltage Rating	106	
7.23	Service Factor		
7.24	Open-Type Motors		
7.25	Overspeeds for Motors		
	7.25.1 Motors Rated 60 Hz and Less		
	7.25.2 Motors Rated 60 Hz Operated at Speeds Above 60 Hz Synchronous Speed		
7.26	Machine Sound—Medium Motors		
7.27	Number of Starts		
	7.27.1 Normal Starting Conditions		
	7.27.2 Other than Normal Starting Conditions	109	
	7.27.3 Considerations for Additional Starts		
7.28	Routine Tests for Polyphase Medium Permanent Magnet Synchronous Motors		
	7.28.1 Method of Testing		
	7.28.2 Typical Tests on Completely Assembled Motors		
	7.28.3 Typical Tests on Motors Not Completely Assembled		
7.29	Thermal Protection of Medium Motors		
	7.29.1 Winding Temperature	110	
7.30	Over Temperature Protection of Medium Motors Not Meeting the Definition of "Thermally		
	Protected"	111	
	7.30.1 Type 1—Winding Running and Locked-Rotor Over Temperature Protection	112	
	7.30.2 Type 2—Winding Running Over Temperature Protection	112	
	7.30.3 Type 3—Winding Over Temperature Protection, Nonspecific Type	112	
7.31	Efficiency	112	
	7.31.1 Determination of Motor Efficiency and Losses	112	
	7.31.2 Efficiency of Polyphase Medium Motors with Continuous Ratings	113	
7.32	Efficiency Levels of Energy-Efficient Polyphase Motors Rated 600 Volts or Less at 60 Hz.		
7.33	Efficiency Level of Premium Efficiency Electric Motors		
	7.33.1 60 Hz Motors Rated 600 Volts or Less		
	7.33.2 60 Hz Motors Rated 601 to 5,000 Volts	115	
	7.33.3 50 Hz Motors Rated 600 Volts or Less		
7.34	Machine with Encapsulated or Sealed Windings—Conformance Test		
7.35	Machine with Moisture-Resistant Windings—Conformance Test	123	

Part 8 App	plication Data—AC Permanent Magnet Small and Medium Machines	
8.0	Scope	. 125
8.1	Proper Selection of Apparatus	. 125
8.2	Usual Service Conditions	
	8.2.1 Environmental Conditions	
	8.2.2 Operating Conditions	. 126
8.3	Unusual Service Conditions	. 126
8.4	Permanent Magnet Generated Voltage	. 127
8.5	Temperature Rise	. 127
	8.5.1 Ambient Temperature at Altitudes for Rated Temperature Rise	. 127
	8.5.2 Motors with Service Factor	. 127
	8.5.3 Temperature Rise at Sea Level	. 127
	8.5.4 Preferred Values of Altitude for Rating Motors	. 127
8.6	Short-Time Rated Electrical Machines	. 127
8.7	Direction of Rotation	. 128
8.8	Application of Pulleys, Sheaves, Sprockets, and Gears on Motor Shafts	. 128
	8.8.1 Mounting	. 128
	8.8.2 Minimum Pitch Diameter for Drives Other than V-Belt	. 128
	8.8.3 Maximum Speed of Drive Components	. 128
8.9	Through-Bolt Mounting	
8.10	Rodent Protection	
8.11	Effects of Variation of Voltage and Frequency Upon the Performance of Permanent Magn	
	Synchronous Motors	
	8.11.1 General	
	8.11.2 Effects of Variation in Voltage on Temperature	. 129
	8.11.3 Effects of Variation in Voltage on Power Factor	
	8.11.4 Effects of Variation in Voltage on Starting Torques	
	8.11.5 Effects of Variation in Frequency	
	8.11.6 Effects of Variations in Both Voltage and Frequency	
	8.11.7 Effects on Special-Purpose or Small Motors	
8.12	Machines Operating on an Ungrounded System	
8.13	Effects of Voltages over 600 Volts on the Performance of Low Voltage Motors	
8.14	Operation of General-Purpose Alternating-Current Polyphase, 2-, 4-, 6-, and 8-Pole, 60 H	
	Medium Permanent Magnet Synchronous Motors Operated on 50 Hertz	
	8.14.1 Speed	
	8.14.2 Torques	
	8.14.3 Locked-Rotor Current	
	8.14.4 Service Factor	
	8.14.5 Temperature Rise	
8.15	Operation of 230-Volt Permanent Magnet Synchronous Motors on 208-Volt Systems	
	8.15.1 General	
	8.15.2 Nameplate Marking of "Usable @ 200 V"	
	8.15.3 Effects on Performance of Motor	
8.16	Effects of Unbalanced Voltages on Motor Performance	
	8.16.1 Effects on Performance—General	
	8.16.2 Unbalance Defined	
	8.16.3 Torques	
	8.16.4 Currents	
8.17	Effects of Power Supply Harmonic Content on Motor Performance	
	8.17.1 Efficiency	
	8.17.2 Derating for Harmonic Content	
8.18	Application of Alternating-Current Motors with Service Factors	
	8.18.1 General	
	8.18.2 Temperature Rise—Medium Alternating-Current Motors	

		8.18.3 Temperature Rise—Small Alternating-Current Motors	135
8	3.19	Coupling End-Play and Rotor Float for Horizontal Alternating-Current Motors	135
		8.19.1 Preferred Ratings for Motors with Ball Bearings	135
		8.19.2 Drawing and Shaft Markings	
8	3.20	Application of Medium Alternating-Current Permanent Magnet Synchronous Machines with	
		Sealed Windings1	
		8.20.1 Usual Service Conditions	135
		8.20.2 Unusual Service Conditions	
		8.20.3 Hazardous Locations	
8	3.21	Application of V-Belt Sheaves to Alternating-Current Motors Having Antifriction Bearings 1	
	). <u> </u>	8.21.1 Dimensions	
		8.21.2 Radial Overhung Load Limitations	
۵	3.22	Aseismatic Capability	
	3.23	Power Factor of Three-Phase Permanent Magnet Synchronous Medium Motors with	100
C	0.20	Continuous Ratings	130
		8.23.1 Determination of Power Factor from Nameplate Data	130
		8.23.2 Determination of Capacitor Rating for Correcting Power Factor to Desired Value . 1	
		8.23.3 Determination of Corrected Power Factor for Specified Capacitor Rating	
		8.23.4 Application of Power Factor Correction Capacitors on Power Systems	140
		8.23.5 Application of Power Factor Correction Capacitors on Motors Operated from	1 40
_		Electronic Power Supply	
	3.24	Bus Transfer or Reclosing	
	3.25	Effects of Load on Motor Efficiency	
	3.26	Reed Frequency of Vertical Machines	
Secti	ion IV	Part 9 Large Motors—Alternating-Current Permanent Magnet Motors 1	41
9	9.1	Scope1	141
9	9.2	Basis of Rating1	
9	9.3	Motor Power and Speed Ratings	
9	9.4	Voltage Ratings	
		9.4.1 Voltage Ratings	
		9.4.2 Preferred Motor Power and Voltage Rating	
g	9.5	Frequencies	
	9.6	Service Factor	
		9.6.1 Service Factor of 1.0	
		9.6.2 Service Factor of 1.15	
		9.6.3 Application of Motors with a Service Factor of 1.15	
7	Toete a	and Performance	
	).7	Temperature Rise	
3	). I	9.7.1 Machines with a 1.0 Service Factor at Rated Load	
		9.7.2 Machines with a 1.15 Service Factor at Service Factor Load	
		9.7.3 Temperature Rise for Ambients Higher than 40°C	
		9.7.4 Temperature Rise for Altitudes Greater than 3,300 Feet (1,000 Meters)	
		9.7.5 Temperature Rise for Air-Cooled Motors for Ambients Lower than 40°C but Not Beld	
_		0°C*	145
	9.8	Code Letters (for Locked-Rotor kVA)	
9	9.9	Torque	
		9.9.1 Standard Torque	
		9.9.2 Motor Torques When Customer Specifies a Custom Load Curve	
	9.10	Load Wk <sup>2</sup> for Permanent Magnet Alternating-Current Polyphase Motors	
9	9.11	Number of Starts	
		9.11.1 Starting Capability1	
		9.11.2 Additional Starts	
		9.11.3 Information Plate	
9	9.12	Overspeeds	147

9.13	Variations from Rated Voltage and Rated Frequency			
	9.13.1 Running			
	9.13.2 Starting			
9.14	Tests			
	9.14.1 Test Methods			
	9.14.2 Routine Tests on Motors Completely Assembled in the Factory	150		
	9.14.3 Routine Tests on Motors Not Completely Assembled in the Factor	y 150		
9.15	High-Potential Test			
	9.15.1 Safety Precautions and Test Procedure	150		
	9.15.2 Test Voltage—Primary Windings	150		
9.16	Motor with Sealed Windings—Conformance Tests	150		
	9.16.1 Test for Stator That Can Be Submerged	150		
	9.16.2 Test for Stator That Cannot Be Submerged	151		
9.17	Motor Sound	151		
9.18	Report of Test Form for Permanent Magnet AC Motors	151		
9.19	Efficiency	151		
	9.19.1 Determination of Motor Efficiency	151		
	9.19.A Efficiency of Permanent Magnet Alternating-Current Large Motors Ratings			
	9.19.B Efficiency Levels of 60 Hz Energy-Efficient Polyphase Random W	ound Large		
	Motors			
	9.19.C Efficiency Levels of Premium Efficiency Large Electric Motors	152		
9.20	Reserved for Future Use	159		
9.21	Reserved for Future Use	159		
9.22	Mechanical Vibration	159		
9.23	Reed Frequency of Vertical Motors			
9.24	Effects of Unbalanced Voltages on the Performance of Permanent Magnet Alternating-			
	Current Motors			
	9.24.1 Effect on Performance—General	160		
	9.24.2 Voltage Unbalance Defined	160		
	9.24.3 Torques	160		
	9.24.4 Currents	160		
9.25	Effects of Power Supply Harmonic Content on Motor Performance	161		
	9.25.1 Efficiency	161		
	9.25.2 Derating for Harmonic Content	161		
	9.25.3 Harmonic Voltage Factor (HVF) Defined	161		
	9.25.4 Power Factor Correction			
Manu	facturing	162		
9.26	Nameplate Marking			
	9.26.1 Alternating-Current Permanent Magnet Motors	162		
9.27	Motor Terminal Housings and Boxes			
	9.27.1 Box Dimensions			
	9.27.2 Accessory Lead Terminations			
	9.27.3 Lead Terminations of Accessories Operating at 50 Volts or Less			
9.28	Embedded Temperature Detectors			
Applic	cation Data			
9.29	Service Conditions			
	9.29.1 General			
	9.29.2 Usual Service Conditions			
	9.29.3 Unusual Service Conditions			
	9.29.4 Permanent Magnet Generated Voltage			
9.30	End-Play and Rotor Float for Coupled Sleeve Bearing Horizontal Permane	nt Magnet		
	Alternating-Current Motors			
	9.30.1 General			
	9.30.2 Limits			

	9.30.3	Marking Requirements	166
9.31	Pulsatii	ng Stator Current in Permanent Magnet Alternating-Current Motors	166
	9.31.1	Torque Pulsations During Starting of Permanent Magnet Motors	167
9.32	Aseismatic Capability		
	9.32.1	General	167
	9.32.2	Frequency Response Spectrum	167
	9.32.3	Units for Capability Requirements	167
	9.32.4	Recommended Peak Acceleration Limits	167
9.33	Belt, Cl	hain, and Gear Drive	168
9.34	Bus Tra	ansfer or Reclosing	168
9.35	Power	Factor Correction	168
9.36	Surge (	Capabilities of AC Windings with Form-Wound Coils	169
	9.36.1	General	169
	9.36.2	Surge Sources	169
	9.36.3	Factors Influencing Magnitude and Rise Time	169
	9.36.4	Surge Protection	169
	9.36.5	Surge Withstand Capability for Standard Motors	169
	9.36.6	Special Surge Withstand Capability	169
	9.36.7	Testing	170
	9.36.8	Test Voltage Values	170
9.37	Motors	Operating on an Ungrounded System	170
9.38	Occasi	onal Excess Current	
	9.38.1	Calculation of Natural Frequency of Permanent Magnet Motor Direct-Co	nnected to
		Reciprocating Machinery	
	9.38.2	Synchronizing Torque Coefficient, Pr	171
	9.38.3	Factors Influencing P <sub>r</sub>	171
9.39	Compre	essor Factors	171

### **Foreword**

This guide has been developed by the Motor and Generator Section and approved for publication as a Standard of the National Electrical Manufacturers Association. It is intended to assist users in the proper selection and application of motors and generators. All persons having experience in the selection, use, or manufacture of electric motors and generators are encouraged to submit recommendations that will improve the usefulness of this guide. Inquiries, comments, and proposed or recommended revisions should be submitted to the Motor and Generator Section by contacting:

NEMA Technical Operations Department National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, VA 22209

The best judgment of the Motor and Generator Section on the performance and construction of motors and generators is represented in this guide. It is based upon sound engineering principles, research, and records of test and field experience. Also involved is an appreciation of the problems of manufacture, installation, and use derived from consultation with and information obtained from manufacturers, users, inspection authorities, and others having specialized experience. For machines intended for general applications, information as to user needs was determined by the individual companies through normal commercial contact with users.

Practical information concerning performance, safety, test, construction, and manufacture of motors within the product scopes defined in the applicable section or sections of this publication is provided in this guide.

In the preparation of this guide, consideration has been given to the work of other organizations whose Standards are in any way related to motors and generators. Credit is hereby given to all those Standards organizations that may have been helpful in the preparation of this volume.

The Standards or guidelines presented in a NEMA Standards publication are considered technically sound at the time they are approved for publication. They are not a substitute for a product seller's or user's own judgment with respect to the particular product referenced in the Standard or guideline, and NEMA does not undertake to guaranty the performance of any individual manufacturer's products by virtue of this Standard or guide. Thus, NEMA expressly disclaims any responsibility for damages arising from the use, application, or reliance by others on the information contained in these Standards or guidelines.

This Standards publication was developed by the Motor and Generator Section. Section approval of the Standard does not necessarily imply that all Section Members voted for its approval or participated in its development. At the time it was approved, the Motor and Generator Section was composed of the following Members:

ABB Motors and Mechanical, Inc.—Fort Smith, AR
Bluffton Motor Works—Bluffton, IN
Brook Crompton North America—Toronto, ON
Cummins, Inc.—Minneapolis, MN
GE Industrial Motors, a Wolong Company—Houston, TX
Nidec Motor Corporation—St. Louis, MO
NORD Gear Corporation—Waunakee, WI
Regal Beloit Corporation—Beloit, WI, composed of:
Marathon Electric Manufacturing Corporation—Wausau, WI

SEW-Eurodrive, Inc.—Lyman, SC
Siemens Industry, Inc.—Norcross, GA
Sterling Electric, Inc.—Indianapolis, IN
Tatung Electric Company of America—Tustin, CA
Techtop Industries, Inc.—Peachtree Corners, GA
TECO-Westinghouse Motor Co.—Round Rock, TX
Toshiba International Corporation—Houston, TX
Turntide Technologies—Sunnyvale, CA
WEG Electric Motor Corp.—Duluth, GA
Worldwide Electric Corporation—Rochester, NY

# Section I General Standards Applying to All Machines Part 1 Referenced Standards and Definitions

### 1.1 Scope

This guide covers general-purpose synchronous motors without excited rotor windings, including polyphase alternating-current permanent magnet motors rated 500 hp and less, designed in Standard ratings with Standard operating characteristics and mechanical construction for use under usual service conditions without restriction to a particular application or type of application, and incorporating all of the following:

- a. Across the line starting
- b. Permanent magnets in the rotor
- c. Open or enclosed construction
- d. Rated continuous duty
- e. Class B or higher rated insulation system with a temperature rise at rated load not exceeding that specified in 7.15 for Class B insulation

#### 1.2 Referenced Standards

The following publications are adopted in whole or in part as indicated, by reference in this Standards publication.

### **American National Standards Institute (ANSI)**

25 West 43rd Street New York, NY 10036

ANSI B92.1-1996	Involute Splines and Inspection
ANSI C84.1-2016	Electric Power Systems and Equipment— Voltage Ratings (60 Hz)
ANSI S12.12-1992 (R2017)	Engineering Method for the Determination of Sound Power Levels of Noise Sources Using Sound Intensity
ANSI S12.35-1990 (R2001)	Precision Methods for the Determination of Sound Power Levels of Noise Sources in Anechoic and Hemi-Anechoic Rooms
ANSI S12.51-2012 (R2017)	Acoustics—Determination of sound power levels and sound energy levels of noise sources using sound pressure—Precision methods for reverberation test rooms
ANSI S12.53-1-2011 (R2016)	Acoustics—Determination of sound power levels of noise sources—Engineering methods for small, movable sources in reverberant fields—Part 1: Comparison method for hard-walled test rooms
ANSI S12.53-2-1999 (R2004)	Acoustics—Determination of sound power levels of noise sources—Engineering methods for small, movable sources in reverberant fields—Part 2: Methods for special reverberation test rooms