NEMA Standards Publication SSL 1-2016

Electronic Drivers for LED Devices, Arrays, or Systems

Published by:

National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

www.nema.org

© 2016 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

NEMA standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

Forewo	rd	.ii	
Sectior	1 General	1	
1.1	Scope	1	
1.2	References		
1.2.1	Normative References	1	
1.2.2	Informative References		
1.3	Definitions	2	
Sectior	Section 2 LED Driver Ratings		
2.1	Common Voltage Ratings (Nominal (Input or Supply) Voltage and Frequency)	4	
2.2	Supply (Input) Ratings.	4	
2.3	Led Load (Array, Module, or Package)		
2.4	Led Driver Operating Temperatures		
Sectior	n 3 Driver Performance		
3.1	General		
3.1.1	Operating Conditions		
3.2	Led Driver Input.		
3.2.1	Operating Supply Voltages		
3.2.2	Input Current Harmonic Distortion		
3.2.3	Input Inrush Current		
3.2.4	Input Current	5	
3.2.5	Input Power		
3.2.6	Power Factor		
3.3	Driver Output		
3.3.1	Constant Voltage Regulated Output		
3.3.2	Constant Current Regulated Output		
3.4	Dimming Regulated Output		
Section 4 EMC Emission and Immunity Requirements			
4.1	Electromagnetic Interference Suppression		
4.2	Line Transient (Surges)	8	
Sectior	n 5 Driver Safety	9	
5.1	Remote Driver	9	
Section 6 Application Requirements			
6.1	Audible Sound Level		
6.2	Power—Temperature Cycle (PTC)		
6.3	Supply Voltage Switching		
6.4	Driver Efficiency		
6.5	Driver Standby Loss		
6.6	Dimming	2	
Section 7 Led Driver Marking			
7.1	Permanent Marking		
7.2	Rated Supply Voltage Designation		
7.3	Output Regulation		

Foreword

The NEMA Ballast and Driver Section has revised this standards publication. In its initial preparation, input of users and other interested parties was sought and evaluated. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product subdivision by contacting:

Senior Technical Director, Operations National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

Section approval of the standard does not necessarily imply that all section members voted for its approval or participated in its development. At the time the standard was approved, the Ballast and Driver Section was composed of the following members:

Acuity Brands, Inc. Advanced Lighting Technologies Inc. Atlas Lighting Products, Inc. Crestron Electronics, Inc. Eaton Lighting Solutions EiKO Global, LLC **GE** Lighting Halco Lighting Technologies Hubbell Lighting, Inc. / Thomas Research Products Leviton Manufacturing Co., Inc. Lumileds LLC Lutron Electronics Company, Inc. **OSRAM SYLVANIA Inc.** Philips Lighting Technical Consumer Products, Inc. Universal Lighting Technologies

Section 1 General

1.1 Scope

This standard provides specifications for and operating characteristics of non-integral electronic drivers (power supplies) for LED devices, arrays, or systems intended for general lighting applications. Electronic drivers are devices that use semiconductors to control and supply dc power for LED starting and operation. The drivers operate from supply sources of 600 V AC or DC maximum at a frequency of 50 or 60 hertz.