NEMA XW 1000-2021

Extruded Insulated Magnet Wire

Published by:

National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, Virginia 22209

www.nema.org

© 2021 National Electrical Manufacturers Association. All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

NEMA Standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus Standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its Standards and guideline publications. NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document.

NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this Standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other Standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

Forewo How to	ord Use Th	is Publication	i ii
Part 1 (General		
1.1	Scope.		3
1.2	References		
	Normative References		
	1.2.1	Normative References	4
	1.2.2	Other References	4
1.3	Definitio	ons	4
1.4	Conductor Materials		
	1.4.1. 1 4 2	Surface Condition	6
1.5	Manufa	cturing	7
-	1.5.1	Application of Insulation	7
	1.5.2	Intermediate Sizes	7
	1.5.3	Joints	7
	1.5.4	Packaging	7
1.6	Test Conditions and Parameters		8
	1.6.1	Safety Statement	8
	1.6.2	Selection of Specimens	8
	1.6.3	Ambient Conditions of Test	8
	1.6.4	Power Frequency	8
	1.6.5	Rectangular and Square Wire	8
	1.6.6	Round Wire	9
	1.6.7	Periodic Conformance	10
	1.6.8	Retests	10
1.7	Units of	Measure	. 10
1.8	Therma	I Class of Extruded Insulated Magnet Wire	. 10
1.9 1.10	Minimum Ordering Data De-Reeling(Winding) Tension		. 10 . 10
Part 2 I Introdu	Properti	es and Requirements	14

Specifications Listing by XW Specification Number, Insulation Material, Thermal Class, Voltage Rating, and Form

Specification Number				Form		
	Construction	Thermal Class	Voltage Rating	Round	Rectangular and Square (Shaped)	Page No.
XW 1-C	Poly(ether ether ketone) Extrusion Coated Copper	240	600	Х	_	16
XW 1-C	Poly(ether ether ketone) Extrusion Coated Copper	240	1000	Х		17
XW 1-C	Poly(ether ether ketone) Extrusion Coated Copper	240	1500	Х		18
XW 2-C	Poly(ether ether ketone) Extrusion Coated Copper	240	600		Х	19
XW 2-C	Poly(ether ether ketone) Extrusion Coated Copper	240	1000		Х	20
XW 2-C	Poly(ether ether ketone) Extrusion Coated Copper	240	1500		Х	21
XW 3-C	Poly(ether ether ketone) Extrusion Coated Copper	250	600	Х		22
XW 3-C	Poly(ether ether ketone) Extrusion Coated Copper	250	1000	Х		23
XW 3-C	Poly(ether ether ketone) Extrusion Coated Copper	250	1500	Х		24
XW 4-C	Poly(ether ether ketone) Extrusion Coated Copper	250	600		Х	25
XW 4-C	Poly(ether ether ketone) Extrusion Coated Copper	240	1000		Х	26
XW 4-C	Poly(ether ether ketone) Extrusion Coated Copper	250	1500		Х	27
XW 5-A	Polyphenylsulfone Extruded Insulated Aluminum	200			Х	28
XW 5-C	Polyphenylsulfone Extruded Insulated Copper	200			Х	29

Appendices

Appendix A	Cross Reference of Extruded Insulated Magnet Wire Test Conditions
and Procedures	A-1

Figures

Figure 1-3-1	Full Rounded Edge	.5
Figure 1-3-2	Rounded Corner	.5

Foreword

This is the first edition of NEMAXW 1000-2021. This Standard is periodically reviewed by the NEMA Magnet Wire Section for revisions considered to be necessary to keep it up to date with changes in technology and regulations.

Proposed or recommended revisions should be submitted to:

NEMA Technical Operations Department National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, VA 22209

XW 1000 was developed by the Extruded Magnet Wire Committee of the NEMA Magnet Wire Section, with input from representatives of various magnet wire end-user industries. At the time this edition was approved, the Magnet Wire Section had the following Members:

CONDUMEX	México, D.F., México
Elektrisola, Inc.	Boscawen, NH
Essex Furukawa Magnet Wire LLC	Fort Wayne, IN
Magnekón, s.a. de CV	San Nicolas, NL, México
MWS Wire Industries	Westlake Village, CA
New England Wire Technologies Corporation	Lisbon, NH
Rea Magnet Wire Company, Inc.	Fort Wayne, IN
Virginia Insulated Products, Inc.	Saltville, VA
Zeus Industrial Products, Inc.	Orangeburg, SC

How to Use This Publication

First, review Part 1 for general information. Then in Part 2, locate the specification for the type of insulation and conductor of interest. Part 2 is arranged in numerical order as shown beginning on page 14, with each specification indicating the requirements to be met and the referenced test procedures.

Part 1 of this publication deals with information common to all types of extruded insulated magnet wire: general material requirements, general test conditions, definitions, and manufacturing data in support of thermal rating.

Part 2 consists of product specification requirements for extruded insulated magnet wire with different types of coverings, thermal classes, and voltage ratings. Insofar as possible, the product specifications are complete on one sheet since they are arranged to include only one covering per sheet. The title on each sheet identifies the product. Example: XW 1-C, PEEK extruded insulated round copper wire. Any specification ending with A denotes aluminum wire.

Annex A provides a cross-reference between NEMA, UL, IEC, and ASTM test procedures.

Part 1

< This page intentionally left blank. >

Part 1

General

1.1 Scope

This publication is designed to present in concise and convenient form all existing NEMA Standards for extruded insulated copper and aluminum magnet wire, including round, rectangular and square, for use in electrical apparatus.

Included are the definitions, type designations, dimensions, constructions, performance, and test methods for extruded insulated magnet wire generally used in the winding of coils for electrical apparatus. Unless otherwise stated, a revision to a product specification in this Standards publication does not affect compliance of products manufactured during the time a previous version of that specification was in effect.