NEMA Standards Publication No. XR 15-1991 (R1996, R2001) Test Standard for the Determination of the Visible Entrance Field of an X-Ray Image Intensifier System

Published by:

National Electrical Manufacturers Association 1300 North 17th Street, Suite 1847 Rosslyn, VA 22209

© Copyright 2001 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne

Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

NEMA standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety—related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

TABLE OF CONTENTS

		Page
	FOREWORD	. ü
	INTRODUCTION	iii
	SCOPE	iii
SECTION 1	REFERENCED STANDARDS AND TERMINOLOGY	
	Referenced Standards	. 1
	Degree of Requirements	. 1
	Definitions	. 1
SECTION 2	TEST EQUIPMENT	. 3
SECTION 3	STANDARD TEST CONDITIONS	
	General Requirements	. 5
	Source to Entrance Plane Distance (SED)	
SECTION 4	DETERMINATION	
	Measurement Procedures	. 7
	Presentation of Results	
SECTION 5	STATEMENT OF COMPLIANCE	9
FIGURE	Figure 2-1 Image Position Calibration Template	
	1 15 m 2 1 m mgc 1 Ostdon Cantoladon 1 cmplate	. د

Foreword

This NEMA Standards Publication is one of a series of test standards developed by the X-ray Imaging Products Section and the medical diagnostic imaging industry for the measurement of performance characteristics governing the image quality of X-ray image intensifier (XRII) systems. These test standards are intended for the use of equipment manufacturers, prospective purchasers, and users alike. Manufacturers may find these standards useful in establishing standard test conditions for the determination of system performance specifications. Prospective equipment purchasers may benefit from these standards as the employment of standard test conditions and methods enables meaningful comparisons to be made of NEMA-referenced, competitive, equipment performance specifications. Users may also benefit from these standards through a better appreciation of the performance of XRII systems.

Characterizing the parameters that govern image quality is a non-trivial task. The assessment of image quality lies in the eye of the beholder and so is a somewhat subjective measure influenced by the spatial, temporal, contrast, and noise characteristics of the image. Historically, many techniques have been developed employing varying degrees of sophistication to establish subjective and objective measures of these parameters, and the following non-exhaustive list of parameters can be considered as relevant to image quality:

Contrast Ratio
Detective Quantum Efficiency (DQE)
Fixed Pattern Noise
Gain
Image Signal Uniformity
Lag
Limiting Spatial Resolution
Modulation Transfer Function (MTF)
Noise Power Spectrum
Radial Image Distortion
Signal to Noise Ratio

Visible Entrance Field Size

These parameters are not all independent and some of them may partially overlap in assessing the image quality. Moreover, it must be recognized that not all of these parameters lend themselves to measurement at the installation site. Some parameters require instrumentation better suited to factory measurements while others require the facilities of an instrumentation laboratory to assure the stable test conditions necessary for reliable measurements. The NEMA X-ray Image Intensifier Systems Subcommittee intends to make a selection from the above-mentioned list of parameters where practical and technically feasible measurements can be made at the system level and to prepare a set of NEMA standards.

This publication has been prepared by the X-Ray Imaging Products Section of NEMA which periodically reviews it for revisions necessary to keep it up to date with advancing technology.

Comments or proposed revisions are welcomed and should be submitted to:

Vice-President, Engineering Department National Electrical Manufacturers Association 2101 L Street, N.W., Suite 300 Washington, D.C. 20037

Introduction

This document defines the NEMA test standard method for the determination of the visible entrance field size of an X-ray image intensifier (XRII) system. These systems include direct viewing systems, video systems, photofluorographic film recording systems, and cine film recording and projection systems.

The visible entrance field size is a measure of the area imaged by an X-ray image intensifier system.

Scope

The procedures in this standard determine the visible entrance field size of an X-ray image intensifier system.